



HAL
open science

AlGaN-based MQWs emitting at 280nm for Vertical Cavity Surface Emitting Lasers

Gaëlle Le Gac, Xin Li, Suresh Sundaram, Youssef El Gmili, Tarik Moudakir, Pierre Disseix, François Reveret, Delphine Lagarde, Joël Leymarie, Sophie Bouchoule, et al.

► **To cite this version:**

Gaëlle Le Gac, Xin Li, Suresh Sundaram, Youssef El Gmili, Tarik Moudakir, et al.. AlGaN-based MQWs emitting at 280nm for Vertical Cavity Surface Emitting Lasers. Conference on Lasers and Electro-Optics, Jun 2015, Munich, Germany. hal-01257060

HAL Id: hal-01257060

<https://hal.science/hal-01257060>

Submitted on 10 May 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

AlGaIn-based MQWs emitting at 280nm for Vertical Cavity Surface Emitting Lasers

G. Le Gac¹, X. Li^{2,3}, S. Sundaram³, Y. El Gmili³, T. Moudakir³, P. Disseix¹, F. Réveret¹, Delphine Lagarde⁴, J. Leymarie¹, S. Bouchoule⁵, G. Patriarche⁵, F. Genty⁶, J-P. Salvestrini^{3,7}, R. D. Dupuis⁸, P. L. Voss^{2,3}, A. Ougazzaden^{2,3}

1. Institut Pascal UMR 6602 CNRS, Université Blaise Pascal, 63171 Aubière, France
2. School of Electrical and Computer Engineering, Georgia Institute of Technology, GT-Lorraine, 57070 Metz, France
3. UMI 2958, Georgia Tech - CNRS, 57070 Metz, France
4. Université de Toulouse, LPCNO, INSA-CNRS-UPS, 135 Avenue de Rangueil, Toulouse, France
5. LPN CNRS, UPR20, 91460 Marcoussis, France
6. Supelec, LMOPS, EA4423, 57070 Metz, France
7. Université de Lorraine, LMOPS, EA 4423, 57070 Metz, France
8. Center for Compound Semiconductors and School of Electrical and Computer Engineering, Georgia Institute of Technology, Atlanta, Georgia 30332,

There is currently much research in deep ultraviolet (DUV: $\lambda < 300$ nm) III-nitride based light sources that would enable a wide variety of potential applications such as sterilization and high density storage systems [1]. Indeed, it is necessary to develop emitters that are more compact and more stable than common UV lamps for these applications to become practical. In this context, innovative solutions must be found for the realization of Vertical Cavity Surface-Emitting Lasers (VCSELs) operating in the DUV spectral range. The primary barriers to be overcome in the active region of DUV light sources based on AlGaIn/AlGaIn heterostructures are: (i) the high dislocation density of Al-rich AlGaIn epilayers on sapphire or SiC substrates, (ii) the strong quantum-confined Stark effect (QCSE) which leads to the reduction of the emission efficiency and (iii) the anisotropic optical polarization properties of c-plane AlGaIn alloys, which are detrimental to surface-emission [2, 3].

We report on the design, fabrication and characterisation of MQW structures containing four or ten Al_{0.57}Ga_{0.43}N/Al_{0.37}Ga_{0.63}N quantum wells (QWs) grown by Metal Organic Vapor Phase Epitaxy on a relaxed Al_{0.57}Ga_{0.43}N buffer grown on an AlN/sapphire template. For the design of the MQW structure, envelop function simulations taking into account strain and built-in electric fields were performed. The relative oscillator strengths were calculated by evaluating the matrix element between conduction and valence bands. To achieve emission near 280 nm, an Al composition, $x_{Al}=0.37$ and a thickness of 1.7 nm (negligible field effects) were estimated from calculations. The optimal Al content in barriers was chosen to be $x_{Al}=0.57$, for which the compressive strain (-0.5%) introduced in the wells is sufficient to enhance TE-polarized optical transition and therefore surface emission [4]. A relaxed AlGaIn buffer with the same Al content was used to release strain in the barriers.

Structural and optical characterizations have been performed to optimize growth conditions and to assess suitable optical quality of the DUV MQW structures. Four- (Fig.1.a) and ten-MQW (Fig.1.b) structures exhibit an emission peak at 285 and 278.5 nm respectively, with a sharp linewidth at 77 K. Transmission measurements combined with numerical simulations confirm a sufficient oscillator strength leading to an optical absorption coefficient in the wells as high as 2.5×10^5 cm⁻¹, which is promising for efficient surface-emitting devices in the DUV region. Complementary time-resolved photoluminescence measurements will be analyzed and further developments related to fabrication of the surrounding cavity will be presented.

This work is supported by ANR (Agence Nationale de la Recherche) - VESUVE (ANR-11-BS03-0012).




Fig. 1: Macro-transmission measurements and transfer-matrix simulations of the MQW structures, absorption coefficients (α_{well} , $\alpha_{barrier}$, buffer) used in the simulation and micro-photoluminescence spectra for the structures containing 4 (left) and 10 (right) QWs.

References

- [1] A. Khan, *Ultraviolet light-emitting diodes based on group three nitrides*, Nature Photonics **2**, 77 - 84 (2008)
- [2] K.B. Nam, *Unique optical properties of AlGaIn alloys and related ultraviolet emitters*, APL **84**, 5264 (2004)
- [3] Wierer, J. J., *Effect of thickness and carrier density on the optical polarization of Al_{0.44}Ga_{0.56}N/Al_{0.55}Ga_{0.45}N quantum well layers*, JAP, **115**, 174501 (2014)
- [4] X. Li, *AlGaIn-based MQWs grown on a thick relaxed AlGaIn buffer on AlN templates emitting at 285 nm*, Optical Materials Express, (2015, to be published)