



Minimum principle for the flow of inelastic non-Newtonian fluids in macroscopic heterogeneous porous media

Laurent Talon

► To cite this version:

Laurent Talon. Minimum principle for the flow of inelastic non-Newtonian fluids in macroscopic heterogeneous porous media. *Physical Review Fluids*, 2022, 7 (4), pp.L042101. 10.1103/PhysRevFluids.7.L042101 . hal-03845409

HAL Id: hal-03845409

<https://cnrs.hal.science/hal-03845409>

Submitted on 9 Nov 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Minimum principle for the flow of inelastic non-Newtonian fluids in macroscopic heterogeneous porous media

Laurent Talon

Université Paris-Saclay, CNRS, FAST, 91405, Orsay, France.

The minimization of dissipation is a general principle in physics. It stipulates that a non-equilibrium system converges toward a state minimizing the energy dissipation. In fluid mechanics, this principle is well known for Newtonian fluids governed by Stokes equation. It can be formulated as follows: among all admissible velocity fields, the solution of the Stokes equation is the one that minimizes the total viscous dissipation. In this paper, we extend these approaches to non-Newtonian fluids in macroscopic heterogeneous porous media, or fractures. The flow is then governed by a nonlinear Darcy equation that can vary in space. In this case, a minimization principle can still be written depending on the boundary conditions. Moreover, such minimization principle can be derived either for the velocity or pressure field.

I. INTRODUCTION

The minimization of dissipation is a general principle in physics. It stipulates that a non-equilibrium system converges toward a state minimizing the energy dissipation. In fluid mechanics [1], this principle was stated by Helmholtz[2] and demonstrated by Korteweg [3] for Newtonian fluids governed by Stokes equation and with a velocity imposed on its boundary. It can be formulated as follows: given a fluid volume where the velocity is prescribed at its boundary, among all admissible velocity fields, the solution of the Stokes equation is the one that minimizes the viscous dissipation. Since then, this principle has been generalized to different boundary conditions [4]. Another important result is the generalization of this principle to non-Newtonian fluids proposed by Bird [5], which is also the basis of the augmented Lagrangian numerical method [6–9]. In this paper, we aim to extend this approaches to non-Newtonian fluids in macroscopic heterogeneous porous media.

Non-Newtonian fluids are found in many applications related to porous or fractured media. An important industrial application is, for example, enhanced oil recovery (EOR) (see [10–12]). Oil is usually recovered by displacing it with another fluid (e.g. water). The main problem lies in the fact that the displacing fluid is often less viscous, resulting in viscous fingering. The fingering tends to create preferential flow paths, leaving a large fraction of the oil. The idea is then to inject a non-Newtonian fluid in order to prevent fingering. Another interesting application is the description of blood in the capillary network, which should be regarded as a suspension and thus with a non-Newtonian viscosity: shear-thinning or yield stress [13, 14]. Non-Newtonian fluids (cements, polymers, etc.) are also commonly used for fracture sealing [15].

A very recurrent problem when dealing with porous media is that of up-scaling. If the equations of motion are generally well known at the pore scale (typically $\sim 10^{-3}$ m), a particular interest is to understand the flow at much larger scales ($\sim 1 - 10^3$ m). This is usually done by deriving constitutive equations for average quantities at an intermediate scale. This is illustrated by the famous Darcy's law for Newtonian fluids, which relates linearly the mean flow rate to the macroscopic gradient of pressure.

At the microscopic level, Newtonian fluids obey the Stokes equation (neglecting inertia and compressibility):

$$\vec{0} = -\vec{\nabla}p + \mu\Delta\vec{v} \quad \text{and} \quad \vec{\nabla} \cdot \vec{v} = \vec{0}, \quad (1)$$

where $\vec{v}$ is the fluid velocity, p is the pressure and μ the viscosity. After averaging over a large number of pores, it results the Darcy's law[16–18]:

$$\vec{u} = -\frac{\kappa}{\mu}\vec{\nabla}P, \quad (2)$$

where $\vec{u}$ is the volume average of the microscopic velocity field, P is a macroscopic pressure field and κ is the permeability of the porous medium which depends on its nature (rock, sand, clay, etc.).

At the geological scale the type of material may however spatially vary leading to a macroscopic heterogeneous permeability field. The understanding of the large-scale flow then requires the resolution of the heterogeneous Darcy's law:

$$\vec{u} = -\frac{\kappa(\vec{r})}{\mu}\vec{\nabla}P \quad \text{and} \quad \vec{\nabla} \cdot \vec{u} = 0. \quad (3)$$

The $\kappa(\vec{r})$ field can be determined experimentally using different methods (borehole, pumping tests). Many models have also been proposed in the literature, the most popular being parallel strata of different natures or the log-normal distribution (see for example [19–22]). This equation is 2D is also equivalent to the “cubic law” commonly used to solved the flow in heterogeneous fractures [23, 24].

It is also important to remember that this equation is also used to solve the flow in fractures with heterogeneous openings, generally referred to as the Reynolds equation [25–29].

All the above mentioned equations apply to Newtonian fluids. A question that naturally arises is: how should this approach be modified when considering non-Newtonian fluids? While there is a very large variety of non-Newtonian fluids [30–32], there are classical approaches in the case where there is a relationship between shear rate $\dot{\gamma}$ and the shear-stress $\tau(\dot{\gamma})$. The approach (see for instance [33–42]) consists in determining an effective shear rate $\dot{\gamma}_{pm}$ in order to relate it to an effective shear-stress (or viscosity). By defining a typical length scale λ (pore size, grain diameter, $\sqrt{\kappa}$, etc.) and using the average flow velocity u , a typical shear rate $\dot{\gamma}_{eff} \propto u/\lambda$ can be defined. Using the mean pressure gradient, a typical shear stress $\tau_{eff} \propto \lambda \nabla P$ can be defined. The idea is then to use these quantities in the rheological function $\dot{\gamma} = f(\tau)$ to derive a generalization of Darcy’s law in the form : $u \propto f(\nabla P)$, where the pre-factors must be determined (experimentally, numerically or theoretically). It is therefore expected that the flow/pressure curve will keep the overall shape of the rheological curve. Similarly to the permeability, it is also expected that the prefactors should depend on the local structure of the medium. This function should thus vary spatially.

In the present article, we aim to demonstrate that in this case, the flow also obey to a minimum principle. We need to make two hypothesis. First, the local porous medium is assumed to be isotropic, which implies that the velocity field is collinear and opposite to the pressure gradient. The second hypothesis is that the rheological function is an increasing monotonic function and thus inversible.

In this case, it can be assumed that the non-linear heterogeneous Darcy’s law can be written in the form:

$$\vec{u} = -f(\vec{r}; \|\vec{\nabla} P\|) \frac{\vec{\nabla} P}{\|\vec{\nabla} P\|} \quad \text{or} \quad \vec{\nabla} P = -g(\vec{r}; \|\vec{u}\|) \frac{\vec{u}}{\|\vec{u}\|} \quad (4a)$$

$$\text{and} \\ \vec{\nabla} \cdot \vec{u} = 0, \quad (4b)$$

with $f(\vec{r}; y)$ and $g(\vec{r}; y)$ positive monotonically increasing functions of y and $\|\cdot\|$ is the norm operator. It is important to mention that both $f()$ and $g()$ are not necessarily continuous.

In the literature, few works address the principle of minimization in porous media. Matheron [19] (in french) proved this principle for the linear Darcy law and the heterogeneous permeability field (see also [43]). Regarding the nonlinear Darcy equation, a variational principle has been proposed by Knupp and Lage [44] for the pressure field, solution of an anisotropic Darcy-Forchheimer equation in a homogeneous permeability field. The pressure field of the nonlinear Darcy solution thus corresponds to the zero derivative of a certain functional. The main limitations of this approach are that, on the one hand, it assumes that the function is differentiable, which is not always the case. And on the other hand, if it shows that the solution is a local extremum, it does not necessarily the uniqueness of the solution.

This paper represents an extension of this work. We will show that the pressure field but also the velocity field obey a minimization principle for any monotonic nonlinear Darcy law, including the presence of permeability heterogeneities. It is important to note that the present principle, following the approach of [6] for Stokes flow, does not involve the derivative of the functional. This has two consequences. First, the function does not have to be differentiable. The f or g function can therefore be discontinuous as in the case of yield stress fluids [45] or discontinuous shear thickening [46, 47] for example. Second, the principle of the minimum is not only local, which allows to prove the uniqueness of the solution depending on the different boundary conditions.

II. MINIMUM PRINCIPLE FOR THE VELOCITY FIELD

II.1. Pressure imposed boundary condition

We consider here a parallelepipedic domain $\mathcal{V}$ where the pressure is homogeneously imposed on the two opposite sides P_{in} and P_{out} . For simplicity, we will assume a periodic boundary condition on the lateral sides. In this case, the minimum principle states that the field $\vec{u}$, solution of the nonlinear Darcy equation eqs. (4a) with an imposed pressure difference ΔP , is also the minimum among all admissible velocity fields $\vec{v}$ of a functional $\Phi[\vec{v}; \Delta P]$:

$$\vec{u} = \arg \min_{\vec{v} \in \Omega} \Phi[\vec{v}; \Delta P] \quad (5)$$

with

$$\Phi[\vec{v}; \Delta P] = \int G(\vec{r}; \|\vec{v}\|) dr^3 - \Delta P Q[\vec{v}], \quad (6)$$

where the admissible velocities are fields satisfying the divergence free and the periodic lateral boundary condition. $G(\vec{r}; \|\vec{v}\|)$ is defined as:

$$G(\vec{r}; \|\vec{v}\|) = \int_0^{\|\vec{v}\|} g(\vec{r}; y) dy. \quad (7)$$

The functional $Q[\vec{v}] = \int_{outlet} \vec{v} \cdot \vec{dS}$ is the total flow rate associated to the field $\vec{v}$ ($\vec{dS}$ is directed towards the exterior of the domain).

Demonstration First, we define Ω the set of admissible velocity fields satisfying the divergence free conditions and the periodic lateral boundary condition. Multiplying eq. (4a) by any $\vec{v} \in \Omega$, and integrating over the domain, yields to:

$$\forall \vec{v} \in \Omega, \int_{\mathcal{V}} \vec{\nabla} P \cdot \vec{v} dr^3 = - \int_{\mathcal{V}} g(\vec{r}; \|\vec{u}\|) \frac{\vec{u} \cdot \vec{v}}{\|\vec{u}\|} dr^3 \quad (8)$$

Using the divergence free of $\vec{v}$ and the divergence theorem, it follows:

$$\begin{aligned} \forall \vec{v} \in \Omega, - \int_{\mathcal{V}} g(\vec{r}; \|\vec{u}\|) \frac{\vec{u} \cdot \vec{v}}{\|\vec{u}\|} dr^3 &= (P_{out} - P_{in}) \int_{outlet} \vec{v} \cdot \vec{dS} \\ &= -Q[\vec{v}] \Delta P, \end{aligned} \quad (9)$$

where $Q[\vec{v}] = \int_{outlet} \vec{v} \cdot \vec{dS} = - \int_{inlet} \vec{v} \cdot \vec{dS}$ and $\Delta P = P_{in} - P_{out}$.

Now, it will be demonstrated that the field $\vec{u}$, solution of the Darcy's equation eqs. (4a), is also the minimum among all $\vec{v} \in \Omega$ of $\Phi[\vec{v}; \Delta P]$. It is equivalent to prove that:

$$\forall \vec{v} \in \Omega, \Phi[\vec{v} + \vec{u}; \Delta P] - \Phi[\vec{u}; \Delta P] \geq 0. \quad (10)$$

Combining eq. (6) and (9) leads to:

$$\forall \vec{v} \in \Omega, \Phi[\vec{v} + \vec{u}; \Delta P] - \Phi[\vec{u}; \Delta P] = \int_{\mathcal{V}} \{G(\vec{r}; \|\vec{v} + \vec{u}\|) - G(\vec{r}; \|\vec{u}\|)\} dr^3 - \Delta P Q[\vec{v}] \quad (11a)$$

$$= \int_{\mathcal{V}} \left\{ G(\vec{r}; \|\vec{v} + \vec{u}\|) - G(\vec{r}; \|\vec{u}\|) - \frac{g(\|\vec{u}\|)}{\|\vec{u}\|} \vec{u} \cdot \vec{v} \right\} dr^3 \quad (11b)$$

Since $g(\vec{r}; y)$ is an increasing function of y , $G(\vec{r}; y)$ is convex, and thus:

$$G(\vec{r}; \|\vec{v} + \vec{u}\|) - G(\vec{r}; \|\vec{u}\|) \geq g(\vec{r}; \|\vec{u}\|) (\|\vec{u} + \vec{v}\| - \|\vec{u}\|). \quad (12)$$

It follows the required property:

$$\begin{aligned} \forall \vec{v} \in \Omega, \Phi[\vec{v} + \vec{u}; \Delta P] - \Phi[\vec{u}; \Delta P] &\geq \int_{\mathcal{V}} \frac{g(\vec{r}; \|\vec{u}\|)}{\|\vec{u}\|} [\|\vec{u} + \vec{v}\| \|\vec{u}\| - \|\vec{u}\|^2 - \vec{u} \cdot \vec{v}] dr^3 \\ &\geq 0, \end{aligned} \quad (13)$$

where the Cauchy-Schwartz inequality has been used: $(\vec{u} + \vec{v}) \cdot \vec{u} \leq \|\vec{u} + \vec{v}\| \|\vec{u}\|$.

We can make several remarks:

Remark 1 It is instructive to put the solution $\vec{u}$ in eq. (9). Leading to:

$$Q[\vec{u}] \Delta P = \int_{\mathcal{V}} g(\vec{r}; \|\vec{u}\|) \|\vec{u}\| dr^3 > 0. \quad (14)$$

This expression represents an energy balance. Since pressure is a potential energy per unit volume, the term on the left is the difference between the input and output flux of this energy. And the right hand term is the total viscous energy dissipation rate in the domain (see Appendix B). It also shows the expected results that the mean flow rate is always opposed to the mean gradient of pressure.

Remark 2: reversibility $\Phi[\vec{r}; \Delta P]$ has the following symmetry property:

$$\Phi[\vec{v}; -\Delta P] = \Phi[-\vec{v}; \Delta P]. \quad (15)$$

It follows that changing the sign of the pressure difference only changes the direction of the velocity field, not its amplitude distribution. Fluid elements will then follow the same stream lines in the opposite direction.

Remark 3: reciprocal theorem It is worth noting that, in eq. (9), $\vec{v}$ can be any diverging free field. An interesting application of this equation, can be the use of a particular solution (e.g the Newtonian solution) in order to obtain the flow rate-pressure drop relation as in Day & Stone [48] and Boyko & Stone [49].

Remark 4: non-uniform imposed pressure For convenience, it has been assumed that the pressure is imposed uniformly at the edges of the inlet and outlet, as this is what is most natural from an experimental perspective. For more complex pressure distributions, it is then necessary to replace $-\Delta P Q[\vec{v}]$ by $\int_{\partial V} P \vec{v} \cdot \vec{dS}$ in eq. (6), where ∂V represents the boundary surface.

II.2. Examples

Although there is a very large variety of different rheological models, we can explicitly write the functional for the most common ones.

Newtonian (Darcy): In the case of a Newtonian fluid in heterogeneous porous media, the flow satisfies Darcy's law:

$$\nabla P = -\frac{\mu}{\kappa(\vec{r})} \vec{u}. \quad (16)$$

In this case, $g(\vec{r}; \|\vec{u}\|) = \frac{\mu}{\kappa(\vec{r})} \|\vec{u}\|$ yields to:

$$\Phi[\vec{v}; \Delta P] = \int_V \frac{\mu}{2\kappa(\vec{r})} \|\vec{v}\|^2 dr^3 - \Delta P Q[\vec{v}]. \quad (17)$$

Where we find the result proposed by Matheron [19] with the last additional term imposing the boundary pressure. This expression is interesting because it shows the expected result that, to minimize dissipation, it is more favorable to have a higher velocity where the permeability is high. However, it is important to note that the admissible field $\vec{v}$ must satisfy the divergence free condition. This constraint can cause low permeability regions to have high velocity (and vice versa).

Power-law rheology: Another very common rheology is the power-law, where $\tau \propto \dot{\gamma}^n$, with n the flow index. In this case, the heterogeneous Darcy's law [33, 50] can be written:

$$-\vec{\nabla} P = c(\vec{r}) \|\vec{u}\|^{n-1} \vec{u}. \quad (18)$$

This leads to:

$$\vec{u} = \arg \min_{\vec{v} \in \Omega} \left\{ \int_V \frac{c(\vec{r})}{n+1} \|\vec{v}\|^{n+1} dr^3 - \Delta P Q[\vec{v}] \right\}. \quad (19)$$

From this relation, one can recover a scaling analysis for the solution. Indeed for any positive ϵ , multiplying by ϵ^{n+1} do not change the argument of the minimum. It gives then:

$$\vec{u}(\Delta P) = \arg \min_{\vec{v} \in \Omega} \left\{ \int_V \frac{c(\vec{r})}{n+1} \|\epsilon \vec{v}\|^{n+1} dr^3 - \epsilon^n \Delta P Q[\epsilon \vec{v}] \right\} = \frac{1}{\epsilon} \vec{u}(\epsilon^n \Delta P) \quad (20)$$

It follows that the field $\frac{\vec{u}(\vec{r})}{Q}$ is a constant field, independent of the applied pressure difference. Combining this with the symmetry discussed earlier, it follows:

$$Q(\Delta P) \propto \|\Delta P\|^{1/n-1} \Delta P. \quad (21)$$

Herschel-Bulkley: Yield stress fluids are often described by the Herschel-Bulkley rheology, $\tau = \tau_0 + K\dot{\gamma}^n$, where τ_0 is the yield stress. At Darcy's scale, the velocity field can be described by (see [22, 51, 52]):

$$-\nabla P = c(\vec{r})\|\vec{u}\|^{n-1}\vec{u} + g_c(\vec{r})\frac{\vec{u}}{\|\vec{u}\|} \quad (22)$$

where $g_c(\vec{r})$ is the local critical pressure gradient below which there is no flow, $c(\vec{r})$ is a prefactor that depend on the consistency and the local geometry, and n the flow index.

It then follows that $g(\vec{r}; \|\vec{u}\|) = c(\vec{r})\|\vec{u}\|^n + g_c(\vec{r})$. Thus:

$$\Phi[\vec{v}; \Delta P] = \int_{\mathcal{V}} \left[\frac{c(\vec{r})}{n+1} \|\vec{v}\|^{n+1} + g_c(\vec{r})\|\vec{v}\| \right] dr^3 - \Delta P Q[\vec{v}]. \quad (23)$$

It is important to note that this function is not differentiable where $\|\vec{v}\| = 0$.

Forchheimer: Forchheimer's law corresponds to the generalization of Newtonian Darcy's law including the influence of inertia. A relation of the form is generally proposed [53]:

$$\|\vec{\nabla} P\| = A\|\vec{u}\|^3 + B\|\vec{u}\|^2 + C\|\vec{u}\|. \quad (24)$$

Although Forchheimer's law applies to Newtonian fluids, it is thus equivalent to a non-Newtonian fluid (shear thickening). In heterogeneous porous media the constants should depend on the local properties, thus $g(\vec{r}; \|\vec{u}\|) = A(\vec{r})\|\vec{u}\|^3 + B(\vec{r})\|\vec{u}\|^2 + C(\vec{r})\|\vec{u}\|$. It follows:

$$\Phi[\vec{v}; \Delta P] = \int_{\mathcal{V}} \left\{ A(\vec{r})\frac{1}{4}\|\vec{v}\|^4 + B(\vec{r})\frac{1}{3}\|\vec{v}\|^3 + \frac{1}{2}C(\vec{r})\|\vec{v}\|^2 \right\} dr^3 - \Delta P Q[\vec{v}]. \quad (25)$$

II.3. Velocity imposed boundary condition

A similar result can be demonstrated in the case where the normal velocity is prescribed at the boundary. Defining Ω_V the ensemble of velocity satisfying the conservation of mass and sharing the same normal flow rate on the boundary $\partial\mathcal{V}$, one has:

$$\vec{u} = \arg \min_{\vec{v} \in \Omega_V} \Phi[\vec{v}] \quad \text{with} \quad \Phi[\vec{v}] = \int_{\mathcal{V}} G(\vec{r}; \|\vec{v}\|) dr^3. \quad (26)$$

Demonstration: For any $\vec{v} \in \Omega_V$,

$$\Phi[\vec{v}] - \Phi[\vec{u}] \geq \int_{\mathcal{V}} g(\vec{r}; \vec{u})(\|\vec{v}\| - \|\vec{u}\|) dr^3 \quad (27a)$$

$$\geq \int_{\mathcal{V}} \frac{g(\vec{r}; \vec{u})}{\|\vec{u}\|} \vec{u} \cdot (\vec{v} - \vec{u}) dr^3 \quad (27b)$$

$$\geq - \int_{\mathcal{V}} \vec{\nabla} P \cdot (\vec{v} - \vec{u}) dr^3 \quad (27c)$$

$$\geq \oint_{\partial\mathcal{V}} P (\vec{v} - \vec{u}) \cdot d\vec{S} \quad (27d)$$

$$= 0, \quad (27e)$$

because $\vec{u}$ and $\vec{v}$ are sharing the same normal velocity at the boundary.

III. MINIMUM PRINCIPLE FOR THE PRESSURE FIELD

Finally, it is also interesting that a similar results exists for the pressure field with a prescribed value at the boundary. Indeed, calling Θ_P the ensemble of field with a given distribution at the boundary, the pressure field P solution of eq. (4a) minimizes the functional $\Psi[H] : P = \arg \min_{H \in \Theta_P} \Psi[H]$, with

$$\Psi[H] = \int_{\mathcal{V}} F(\vec{r}; \|\vec{\nabla} H\|) dr^3 \quad \text{and} \quad F(\vec{r}; y) = \int_0^y f(\vec{r}; y) dy \quad (28)$$

Demonstration The demonstration is very similar to the previous ones. Using the convexity of the function $F(\vec{r}; y)$, one has for any $H \in \Theta_P$:

$$\Psi[H] - \Psi[P] = \int_{\mathcal{V}} \left(F(\vec{r}; \|\vec{\nabla} H\|) - F(\vec{r}; \|\vec{\nabla} P\|) \right) dr^3 \quad (29a)$$

$$\geq \int_{\mathcal{V}} f(\vec{r}; \|\vec{\nabla} P\|) (\|\vec{\nabla} H\| - \|\vec{\nabla} P\|) dr^3 \quad (29b)$$

$$\geq \int_{\mathcal{V}} \frac{f(\vec{r}; \|\vec{\nabla} P\|)}{\|\vec{\nabla} P\|} (\|\vec{\nabla} H\| \|\vec{\nabla} P\| - \|\vec{\nabla} P\|^2) dr^3 \quad (29c)$$

$$\geq \int_{\mathcal{V}} \frac{f(\vec{r}; \|\vec{\nabla} P\|)}{\|\vec{\nabla} P\|} \vec{\nabla} P \cdot (\vec{\nabla} H - \vec{\nabla} P) dr^3 \quad (29d)$$

$$\geq - \int_{\mathcal{V}} \vec{u} \cdot (\vec{\nabla} H - \vec{\nabla} P) dr^3 \quad (29e)$$

$$\geq - \oint_{\partial \mathcal{V}} (H - P) \vec{u} \cdot d\vec{S} = 0, \quad (29f)$$

because H and P have the same value at the boundary.

Remark It is interesting to note that any minimum of a differentiable functional in the form of $\Psi[h] = \int_{\mathcal{V}} D(\vec{r}; \|\vec{\nabla} h\|) dr^3$, where $D(\vec{r}; y)$ is a convex function of y , allows to define a non-linear Darcy's law. Indeed, using Euler-Lagrange formula, we have:

$$\frac{\partial D}{\partial h} - \sum_i \frac{\partial}{\partial x_i} \frac{\partial D}{\partial h_i} = 0, \quad (30)$$

where we use the notation $h_i \doteq \frac{\partial h}{\partial x_i}$.

Since $\frac{\partial D}{\partial h} = 0$, the vector field:

$$q_i = - \frac{\partial D}{\partial h_i} = - \frac{d(\vec{r}; \|\vec{\nabla} h\|)}{\|\vec{\nabla} h\|} \frac{\partial h}{\partial x_i}, \quad i = 1 \dots 3, \quad (31)$$

with $d(\vec{r}; y) = \partial_y D(\vec{r}; y)$ then satisfies the conservation of mass $\vec{\nabla} \cdot \vec{q} = 0$. This thus defines a system of equations in the form of eq. (4a). We retrieve here the approach of Knupp and Lage [44] for the Forchheimer equation. The only main difference here is that the function $d(\vec{r}; \|\vec{\nabla} h\|)$ may vary in space.

IV. CONCLUSION

In conclusion, we were able to establish a minimization principle for nonlinear heterogeneous Darcy flows. This principle can be applied either to the velocity field or to the pressure field. If the function to be minimized differs slightly according to the boundary conditions constraint, all are based on the integral of the flow-pressure relationship. This shows that the important quantity is not so much the instant energy dissipation rate given by $\vec{u} \cdot \vec{\nabla} P = g(\|\vec{u}\|) \|\vec{u}\|$ (see Appendix B) but rather the cumulative dissipation for the velocity to rise from zero to a given value $\int_0^{\|\vec{u}\|} g(y) dy$. For Newtonian, the two functions are proportional, so the minimization principle represents also a minimization of viscous dissipation.

This principle can also be generalized where the flow is also driven by a body force as discussed in Appendix A.

With a little retrospect, it does not seem too surprising that a minimization principle exists at the Darcy scale. Indeed, if such a principle exists at a microscopic scale, it seems then quite natural that a similar one is applicable for locally averaged quantities. There is however an significant difference between the microscopic and macroscopic aspects. At the macroscopic scale, the constitutive law and thus the energy function can be heterogeneous in space. For instance, if some regions are linear while others are non-linear, this minimization principle is still applicable.

It is worth recalling the different assumptions made in the present work. First of all, this approach is *a priori* limited to non-thixotropic and inelastic fluids because the local rheology has been assumed constant in time and not dependent on the history of the fluid element.

Second, the monotonicity of the flow-pressure curve, $g(\vec{r}; y)$ (resp. $f(\vec{r}; y)$), has been assumed, implying the convexity of the function $G(\vec{r}; y)$ (resp. $F(\vec{r}; y)$). This assumption is indeed necessary to prove the uniqueness of the solution.

For example, for a non-monotonic $g()$ function, imposing a pressure difference could lead to different velocity fields. However, if the function $\Phi[]$ is differentiable, a variational approach could still be used. Each solution of the nonlinear Darcy's law would then correspond to a local extremum of $\Phi[\vec{r}; \Delta P]$.

Another important assumption is the isotropy of the local nonlinear Darcy equation, leading to an alignment of the pressure gradient and the velocity. The first step to generalize to anisotropic media would be to determine a generic nonlinear anisotropic Darcy's law. Knupp and Lage [44] assumed a permeability tensor formulation for the Forchheimer equation. In this case, a variational formulation can be used. We note, however, that more generic and complex formulations have been proposed in the literature. For example, Auriault [54] proposed a formulation involving three principal axes and four functions of the mean pressure gradient for power-law fluids. Here also, a generic Darcy remains to be formulated for any type of rheology and anisotropy to be able to generalize this work. In addition, one of the main difficulties for heterogeneous permeability fields is that the principal axes could potentially also vary in space.

Appendix A: Flow driven by a body force

Another possible condition to drive the flow is the presence of a body force $\vec{G}$ (homogeneous or not). We assume also an imposed pressure difference ΔP between the outlet and inlet as in sec. II.1. In this case Darcy's law can be written as:

$$\vec{\nabla} P - \vec{G}(\vec{r}) = -g(\vec{r}; \|\vec{u}\|) \frac{\vec{u}}{\|\vec{u}\|} \quad (\text{A1})$$

and the minimum principle then reads:

$$\vec{u} = \arg \min_{\vec{v} \in \Omega} \Phi_{\vec{G}}[\vec{v}; \Delta P] \quad (\text{A2})$$

with

$$\Phi_{\vec{G}}[\vec{v}; \Delta P] = \int_V G(\vec{r}; \|\vec{v}\|) dr^3 - \Delta P Q[\vec{v}] - \int_V \vec{G}(\vec{r}) \cdot \vec{v} dr^3. \quad (\text{A3})$$

Indeed, from eq. (A1), we have for any $\vec{v} \in \Omega$:

$$\forall \vec{v} \in \Omega, - \int_V g(\vec{r}; \|\vec{u}\|) \frac{\vec{u} \cdot \vec{v}}{\|\vec{u}\|} dr^3 = \int_V (\vec{\nabla} P - \vec{G}(\vec{r})) \cdot \vec{v} dr^3 \quad (\text{A4a})$$

$$= -Q[\vec{v}] \Delta P - \int_V \vec{G}(\vec{r}) \cdot \vec{v} dr^3. \quad (\text{A4b})$$

It then follows:

$$\forall \vec{v} \in \Omega, \Phi_{\vec{G}}[\vec{v} + \vec{u}; \Delta P] - \Phi_{\vec{G}}[\vec{u}; \Delta P] = \int_V \left\{ G(\vec{r}; \|\vec{u} + \vec{v}\|) - G(\vec{r}; \|\vec{v}\|) - \vec{G}(\vec{r}) \cdot \vec{v} \right\} dr^3 - \Delta P Q[\vec{v}] \quad (\text{A5a})$$

$$= \int_V \left\{ G(\vec{r}; \|\vec{u} + \vec{v}\|) - G(\vec{r}; \|\vec{v}\|) - g(\vec{r}; \|\vec{u}\|) \frac{\vec{u} \cdot \vec{v}}{\|\vec{u}\|} \right\} dr^3 \quad (\text{A5b})$$

$$\geq \int_V \frac{g(\vec{r}; \|\vec{u}\|)}{\|\vec{u}\|} \{ \|\vec{u} + \vec{v}\| \|\vec{u}\| - \|\vec{u}\|^2 - \vec{v} \cdot \vec{u} \} dr^3 \quad (\text{A5c})$$

$$\geq 0. \quad (\text{A5d})$$

Appendix B: Energy dissipation rate for non-linear Darcy's law

In this section, we recall the relationship between Darcy's law and the viscous energy dissipation rate at the microscopic level. We consider a parallelepipedic volume $V = L_1 L_2 L_3$ containing both solid and fluid regions. A uniform pressure is imposed on each side $p_i^{in/out}$ of each direction $i = 1, 2 \dots 3$, and we also assume the absence of any other stress at the boundary. A no-slip condition is assumed at the fluid/solid boundary.

In the fluid region, neglecting inertia, the flow satisfies the Cauchy equation at steady state:

$$\vec{\nabla} \cdot \mathbf{\Pi} - \vec{\nabla} p = \mathbf{0}, \quad (\text{B1})$$

where p is the microscopic pressure and $\mathbf{\Pi}$ is the deviatoric stress tensor. The strain rate tensor is defined as:

$$\Delta_{ij} = \frac{1}{2} \left(\frac{\partial v_i}{\partial x_j} + \frac{\partial v_j}{\partial x_i} \right), \quad (\text{B2})$$

with $\vec{v}$ the microscopic velocity.

Applying the scalar product with $\vec{v}$ in eq. (B1) and averaging over V gives:

$$\frac{1}{V} \int_{V_F} \left\{ (\vec{\nabla} \cdot \mathbf{\Pi}) \cdot \vec{v} - (\vec{\nabla} p) \cdot \vec{v} \right\} dr^3 = 0. \quad (\text{B3})$$

Here, V_F stands for the volume of fluid inside V .

The two terms are analyzed separately. The first term reads:

$$\int_{V_F} (\vec{\nabla} \cdot \mathbf{\Pi}) \cdot \vec{v} dr^3 = \int_{V_F} \sum_{ij} (\partial_i \Pi_{ij}) v_j dr^3 = \int_{V_F} \sum_{ij} \{ \partial_i (\Pi_{ij} v_j) - \Pi_{ij} \partial_i v_j \} dr^3 \quad (\text{B4})$$

$$= - \int_{V_F} \sum_{ij} \Pi_{ij} \Delta_{ij} dr^3 + \int_{\partial V_F} \sum_{ij} (\Pi_{ij} v_j) dS_i \quad (\text{B5})$$

The second term in this equation is a surface integral on the fluid boundary. There are two types of boundaries. At the boundary between solid and fluid, the velocity is zero due to the no-slip condition. And at the boundary of the domain, the deviatoric stress is zero. For these two reasons, the surface integral is zero. It results:

$$\frac{1}{V} \int_{V_F} (\vec{\nabla} \cdot \mathbf{\Pi}) \cdot \vec{v} dr^3 = - \frac{1}{V} \int_{V_F} \sum_{ij} \Pi_{ij} \Delta_{ij} dr^3. \quad (\text{B6})$$

The first term of eq. (B3) thus represents the average viscous dissipation within the porous medium.

The second term in this equation writes:

$$\int_{V_F} (\vec{\nabla} p) \cdot \vec{v} dr^3 = \int_{V_F} \vec{\nabla} \cdot (p \vec{v}) dr^3 = \int_{\partial V_F} p \vec{v} \cdot \vec{dS} \quad (\text{B7})$$

This integral is zero at the solid/fluid boundary. Since the pressure is uniform on each side of the domain, it gives:

$$\int_{V_F} (\vec{\nabla} p) \cdot \vec{v} dr^3 = \sum_i (q_i^{\text{out}} p_i^{\text{out}} - q_i^{\text{in}} p_i^{\text{in}}), \quad (\text{B8})$$

with $q_i^{\text{in/out}}$ represents the velocity flux at the two boundary in the direction i . In the homogenization procedure, these flows are assumed to be equal at first order. This allows to define the mean velocity component $u_i = q_i / S_i$ and the mesoscopic pressure gradient $\vec{\nabla} P = \frac{p_i^{\text{out}} - p_i^{\text{in}}}{L_i}$. It follows that

$$\frac{1}{V} \int_{V_F} (\vec{\nabla} p) \cdot \vec{v} dr^3 = \sum_i u_i \frac{p_i^{\text{out}} - p_i^{\text{in}}}{L_i} = \vec{u} \cdot \vec{\nabla} P \quad (\text{B9})$$

Combining eqs. (B3), (B6) and (B9) thus shows that at the Darcy's scale, the term

$$\vec{u} \cdot \vec{\nabla} P = -g(\vec{r}; \|\vec{u}\|) \|u\| = -f(\vec{r}; \|\vec{\nabla} P\|) \|\vec{\nabla} P\| = -\frac{1}{V} \int_{V_F} \sum_{ij} \Pi_{ij} \Delta_{ij} dr^3, \quad (\text{B10})$$

represents the averaged microscopic energy dissipation rate.

ACKNOWLEDGMENTS

I would like to thank Dominique Salin, Jean-Pierre Hulin, Alex Hansen and Alberto Rosso for very fruitful discussions.

-
- [1] J. Happel and H. Brenner, *Low Reynolds number hydrodynamics* (D. Reidel Publishing Co., Hingham, MA, 1983).
 - [2] H. v. Helmholtz, Zur theorie der stationären ströme in reibenden flüssigkeiten, *Wiss. Abh* **1**, 223 (1868).
 - [3] D. Korteweg, Xvii. on a general theorem of the stability of the motion of a viscous fluid, *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science* **16**, 112 (1883),.
 - [4] J. B. Keller, L. A. Rubinfeld, and J. E. Molyneux, Extremum principles for slow viscous flows with applications to suspensions, *Journal of Fluid Mechanics* **30**, 97 (1967).
 - [5] R. B. Bird, New variational principle for incompressible non-newtonian flow, *The Physics of Fluids* **3**, 539 (1960),.
 - [6] G. Duvaut and J. L. Lions, *Inequalities in mechanics and physics* (Springer, 1976).
 - [7] M. Fortin and R. Glowinski, The augmented lagrangian method (1983).
 - [8] R. Glowinski and P. Le Tallec, *Augmented Lagrangian and operator-splitting methods in nonlinear mechanics*, Vol. 9 (SIAM, 1989).
 - [9] P. Saramito and N. Roquet, An adaptive finite element method for viscoplastic fluid flows in pipes, *Computer methods in applied mechanics and engineering* **190**, 5391 (2001).
 - [10] K. Sorbie, P. Clifford, and E. Jones, The rheology of pseudoplastic fluids in porous media using network modeling, *J. Colloid Interface Sci.* **130**, 508 (1989).
 - [11] K. S. Sorbie, *Polymer-improved oil recovery* (Springer, Dordrecht, 1991).
 - [12] I. A. Frigaard, K. G. Paso, and P. R. de Souza Mendes, Bingham’s model in the oil and gas industry, *Rheologica Acta* **56**, 259 (2017).
 - [13] J. Boyd, J. M. Buick, and S. Green, Analysis of the Casson and Carreau-Yasuda non-Newtonian blood models in steady and oscillatory flows using the lattice Boltzmann method, *Phys. Fluids* **19**, 093103 (2007),.
 - [14] N. Bessonov, A. Sequeira, S. Simakov, Y. Vassilevskii, and V. Volpert, Methods of blood flow modelling, *Math. Model. Nat. Phenom.* **11**, 1 (2016).
 - [15] P. Tongwa, R. Nygaard, A. Blue, and B. Bai, Evaluation of potential fracture-sealing materials for remediating CO2 leakage pathways during CO2 sequestration, *Int. J. Greenhouse Gas Control* **18**, 128 (2013).
 - [16] H. Darcy, *Les fontaines publiques de la ville de Dijon: exposition et application* (Victor Dalmont, 1856).
 - [17] S. Whitaker, Flow in porous media i: A theoretical derivation of Darcy’s law, *Transport in Porous Media* **1**, 3 (1986).
 - [18] J. Bear, *Dynamics of Fluids in Porous Media*, edited by Dover (Elsevier, New York, 1988).
 - [19] G. Matheron, *Éléments pour une théorie des milieux poreux* (Masson Paris, 1967).
 - [20] L. Gelhar and C. Axness, Three-dimensional stochastic analysis of macrodispersion in aquifers, *Water Resour. Res.* **19**, 161 (1983).
 - [21] P. Renard and G. de Marsily, Calculating equivalent permeability: A review, *Adv. Water Resour.* **20**, 253 (1997).
 - [22] R. Kostenko and L. Talon, Numerical study of Bingham flow in macroscopic two dimensional heterogeneous porous media, *Physica A: Statistical Mechanics and its Applications* **528**, 121501 (2019).
 - [23] Y. W. Tsang and P. A. Witherspoon, Hydromechanical behavior of a deformable rock fracture subject to normal stress, *Journal of Geophysical Research: Solid Earth* **86**, 9287 (1981),.
 - [24] S. R. Brown, Fluid flow through rock joints: The effect of surface roughness, *Journal of Geophysical Research: Solid Earth* **92**, 1337 (1987),.
 - [25] O. Reynolds, On the theory of lubrication and its application to Mr. Beauchamp tower’s experiments, including an experimental determination of the viscosity of olive oil, *Phil. Trans. R. Soc. Lond.* **177**, 157 (1886).
 - [26] R. Zimmerman, S. Kumar, and G. Bodvarsson, Lubrication theory analysis of the permeability of rough-walled fractures, *Int. J. Rock Mech. Min. Sci. & Geomech. Abstr.* **28**, 325 (1991).
 - [27] V. Mourzenko, J.-F. Thovert, and P. Adler, Permeability of a single fracture; validity of the Reynolds equation, *J. Phys. II France* **5**, 465 (1995).
 - [28] D. R. Hewitt, M. Daneshi, N. J. Balmforth, and D. M. Martinez, Obstructed and channelized viscoplastic flow in a Hele-Shaw cell, *Journal of Fluid Mechanics* **790**, 173–204 (2016).
 - [29] A. Roustaei, T. Chevalier, L. Talon, and I. A. Frigaard, Non-Darcy effects in fracture flows of a yield stress fluid, *Journal of Fluid Mechanics* **805**, 222 (2016).
 - [30] R. B. Bird, Useful non-Newtonian models, *Annu. Rev. Fluid Mech.* **8**, 13 (1976),.
 - [31] R. B. Bird, R. Armstrong, and O. Hassager, *Dynamics of polymeric liquids. Vol. 1: Fluid mechanics* (John Wiley and Sons Inc., New York, NY, 1987).
 - [32] P. Coussot, *Rheometry of pastes, suspensions, and granular materials: applications in industry and environment* (John Wiley and Sons, 2005).
 - [33] R. H. Christopher and S. Middleman, Power-law flow through a packed tube, *Ind. Eng. Chem. Fundamen.* **4**, 422 (1965).
 - [34] T. J. Sadowski and R. B. Bird, Non-Newtonian flow through porous media. i. theoretical, *Trans. Soc. Rheol.* **9**, 243 (1965),.
 - [35] R. M. McKinley, H. O. Jahns, W. W. Harris, and R. A. Greenkorn, Non-Newtonian flow in porous media, *AIChE Journal*

- 12**, 17 (1966),.
- [36] J. C. Slattery, Flow of viscoelastic fluids through porous media, *AIChE Journal* **13**, 1066 (1967),.
 - [37] G. Hirasaki, G. Pope, *et al.*, Analysis of factors influencing mobility and adsorption in the flow of polymer solution through porous media, *Soc. Pet. Eng. J.* **14**, 337 (1974).
 - [38] G. Chauveteau, Rodlike polymer solution flow through fine pores: Influence of pore size on rheological behavior, *J. Rheol.* **26**, 111 (1982), <https://doi.org/10.1122/1.549660>.
 - [39] J. Pearson and P. Tardy, Models for flow of non-Newtonian and complex fluids through porous media, *J. Non-Newtonian Fluid Mech.* **102**, 447 (2002).
 - [40] X. Lopez, P. H. Valvatne, and M. J. Blunt, Predictive network modeling of single-phase non-Newtonian flow in porous media, *J. Colloid Interface Sci.* **264**, 256 (2003).
 - [41] T. Sochi and M. J. Blunt, Pore-scale network modeling of ellis and herschel-bulkley fluids, *J. Pet. Sci. Eng.* **60**, 105 (2008).
 - [42] M. T. Balhoff and K. E. Thompson, Modeling the steady flow of yield-stress fluids in packed beds, *AIChE J.* **50**, 3034 (2004).
 - [43] B. Nøttinger, An explicit formula for computing the sensitivity of the effective conductivity of heterogeneous composite materials to local inclusion transport properties and geometry, *Multiscale Modeling & Simulation* **11**, 907 (2013).
 - [44] P. Knupp and J. Lage, Generalization of the Forchheimer-extended Darcy flow model to the tensor permeability case via a variational principle, *Journal of Fluid Mechanics* **299**, 97 (1995).
 - [45] R. Bird, R. Armstrong, and O. Hassager, *Dynamics of polymeric liquids. Vol. 1, 2nd Ed. : Fluid mechanics* (John Wiley and Sons Inc., New York, NY, 1987).
 - [46] H. A. Barnes, Shear-thickening (“dilatancy”) in suspensions of nonaggregating solid particles dispersed in Newtonian liquids, *Journal of Rheology* **33**, 329 (1989), <https://doi.org/10.1122/1.550017>.
 - [47] E. Brown and H. M. Jaeger, Shear thickening in concentrated suspensions: phenomenology, mechanisms and relations to jamming, *Reports on Progress in Physics* **77**, 046602 (2014).
 - [48] R. F. Day and H. A. Stone, Lubrication analysis and boundary integral simulations of a viscous micropump, *Journal of Fluid Mechanics* **416**, 197–216 (2000).
 - [49] E. Boyko and H. A. Stone, Reciprocal theorem for calculating the flow rate–pressure drop relation for complex fluids in narrow geometries, *Phys. Rev. Fluids* **6**, L081301 (2021).
 - [50] C. B. Shah and Y. C. Yortsos, Aspects of flow of power-law fluids in porous media, *AIChE J.* **41**, 1099 (1995).
 - [51] V. Entov, On some two-dimensional problems of the theory of filtration with a limiting gradient., *Prikl. Mat. Mekh.* **31**, 820 (1967).
 - [52] D. Bauer, L. Talon, Y. Peysson, H. B. Ly, G. Batôt, T. Chevalier, and M. Fleury, Experimental and numerical determination of Darcy’s law for yield stress fluids in porous media, *Phys. Rev. Fluids* **4**, 063301 (2019).
 - [53] P. Forchheimer, Wasserbewegung durch boden, *Z. Ver. Deutsch. Ing.* **45**, 1782 (1901).
 - [54] J.-L. Auriault, P. Royer, and C. Geindreau, Filtration law for power-law fluids in anisotropic porous media, *Int. J. Eng. Sci.* **40**, 1151 (2002).