



HAL
open science

Prediction of the removal efficiency of emerging organic contaminants in constructed wetlands based on their physicochemical properties

Huma Ilyas, Ilyas Masih, Eric D van Hullebusch

► **To cite this version:**

Huma Ilyas, Ilyas Masih, Eric D van Hullebusch. Prediction of the removal efficiency of emerging organic contaminants in constructed wetlands based on their physicochemical properties. *Journal of Environmental Management*, 2021, 294, pp.112916. 10.1016/j.jenvman.2021.112916 . hal-03901824

HAL Id: hal-03901824

<https://cnrs.hal.science/hal-03901824>

Submitted on 13 Jun 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

1 Prediction of the removal efficiency of emerging organic contaminants in constructed 2 wetlands based on their physicochemical properties

3

4 Huma Ilyas^{1,3*}, Ilyas Masih^{2,3}, Eric D. van Hullebusch¹

5 ¹ Université de Paris, Institut de physique du globe de Paris, CNRS, F-75005 Paris, France

6 ² IHE Delft, Institute for Water Education, 2611 AX Delft, The Netherlands

7 ³ Water Treatment and Management Consultancy, B.V., 2289 ED Rijswijk, The Netherlands

8 * Corresponding author email: hi.wtmconsult@gmail.com

9 Abstract

10 This study investigates the prediction of the removal efficiency of emerging organic
11 contaminants (EOCs) (pharmaceuticals-PhCs, personal care products-PCPs, and steroidal
12 hormones-SHs) in constructed wetlands based on their physicochemical properties (e.g.,
13 molecular weight-MW, octanol-water partition coefficient-Log Kow, soil organic carbon
14 sorption coefficient-Log Koc, octanol-water distribution coefficient-Log Dow, and
15 dissociation constant-pKa). The predictive models are formed based on statistical analysis
16 underpinned by principle component, correlation, and regression analyses of a global data set
17 compiled from peer-reviewed publications. The results show that the physicochemical
18 properties of EOCs emerged as good predictors of their removal efficiency. Log Koc, Log
19 Dow, and Log Kow are the most significant predictors, and combination with MW and/or
20 pKa often improved the reliability of the predictions. The best performing model for PhCs
21 was composed of MW, Log Dow, and Log Koc (coefficient of determination- R^2 : 0.601;
22 probability value- $p < 0.05$; root mean square error-RMSE: training set: 11%; test set: 27%).
23 Log Kow and Log Koc for PCPs (R^2 : 0.644; $p < 0.1$; RMSE: training set: 14%; test set: 14%),
24 and a combination of MW, Log Kow, and pKa for SHs (R^2 : 0.941; $p < 0.1$; RMSE: training

25 set: 3%; test set: 15%) formed the plausible models for predicting the removal efficiency.
26 Similarly, reasonably good combined models could be formed in the case of PhCs and SHs or
27 PCPs and SHs, although their individual models were comparatively better. A novel decision
28 support tool, named as REOCW-PCP, was developed to readily estimate the removal
29 efficiency of EOCs, and facilitate the decision-making process.

30 **Key words:** Constructed wetlands; Personal care products; Pharmaceuticals; Physicochemical
31 properties; Predictive models; Steroidal hormones.

32 **1. Introduction**

33 Pharmaceuticals (PhCs), personal care products (PCPs), and steroidal hormones (SHs) are
34 among the emerging organic contaminants (EOCs) that are discharged to water resources and
35 environment through various sources such as domestic wastewater, industrial wastewater,
36 landfill leachate, runoff from concentrated animal feeding operations and aquaculture, and
37 effluent discharge from wastewater treatment plants (e.g., Luo et al., 2014; Barbosa et al.,
38 2016; Yi et al., 2017; Yin et al., 2019). Although EOCs are often present in relatively small
39 concentrations (i.e., ng L⁻¹ to µg L⁻¹) in water resources, their occurrence as individual
40 compounds, transformation products, and multitude of compounds can still cause negative
41 impacts on human health as well as aquatic and terrestrial life (e.g., Vymazal et al., 2015;
42 Vystavna et al., 2017; Tran et al., 2018). It is well established that the higher concentration of
43 EOCs compared with their potential no effect concentration could pose severe risk to human
44 health, since many of these EOCs are considered as prospective endocrine disruptors
45 (Caliman and Gavrilesco, 2009; Töre et al., 2012; Gogoi et al., 2018).

46 Constructed wetlands (CWs) are environmentally friendly, cost-effective, and nature-based
47 treatment technologies that have been extensively investigated and practically used for the
48 removal of EOCs from the wastewater (e.g., Zhang et al., 2014; Verlicchi et al., 2015; Gorito

49 et al., 2017; Vo et al., 2018). To date, a large number of individual case studies have been
50 published in peer-reviewed journals related to the removal of EOCs by CWs. A review study
51 by Ilyas et al. (2020) indicated that investigation of the impact of physicochemical properties
52 on the removal efficiency has been an important research topic among other thematic areas
53 such as evaluation of the performance of different types of CWs, role of design and
54 operational factors on the treatment process, and environmental risk assessment. There is an
55 increasing evidence that physicochemical properties of EOCs (molecular weight-MW, water
56 solubility-WS, octanol-water partition coefficient-Log Kow, soil organic carbon sorption
57 coefficient-Log Koc, octanol-water distribution coefficient-Log Dow, Henry's law constant-
58 HC, dissociation constant-pKa, and charge at pH 7) play a very important role during the
59 treatment process (Supplementary materials 1: Tables S1), and considerably influencing the
60 possible removal mechanisms such as biodegradation, adsorption/sorption, and plant uptake
61 (e.g., Zhang et al., 2012a, 2012b, 2018; Verlicchi et al., 2013; Vystavna et al., 2017; Ilyas et
62 al., 2020; Ilyas and van Hullebusch, 2019, 2020a, 2020b, 2020c, 2020d).

63 Few experimental studies have indicated an inverse relationship between Log Dow and the
64 removal efficiency of PhCs (e.g., Lee et al., 2011; Zhang et al., 2012b, 2018). However, the
65 resulting correlations were not very strong (e.g., coefficient of determination- R^2 : ~ 0.3) by the
66 study of Zhang et al. (2012b) on horizontal subsurface flow constructed wetland (HFCW); but
67 the relationship was statistically significant (e.g., probability value- $p < 0.1$). Zhang et al.
68 (2018) reported a strong inverse relationship between the removal efficiency and Log Dow
69 (R^2 : 0.82-0.86; $p < 0.05$) in two FWSCWs. These studies indicated some potential of using
70 Log Dow as a predictor of the removal efficiency of PhCs, and highlighted the important role
71 of hydrophobicity in the removal mechanisms of PhCs in CWs. However, the results should
72 be interpreted with caution because these are based on only few individual studies involving a
73 limited number of PhCs (e.g., < 10). Moreover, the proposed regression models are only

74 based on the training data sets. A validation step on an independent test set was not carried
75 out, which limits the reliability and wider application of the proposed models.

76 On the other hand, some studies suggested a non-significant correlation between Log Kow
77 and the removal efficiency of PhCs (Park et al., 2009; Lee et al., 2011; Breitholtz et al., 2012;
78 Zhang et al., 2012a, 2012b). For example, Breitholtz et al. (2012) reported a non-significant
79 correlation ($p > 0.35$) between the removal efficiency of PhCs and Log Kow in FWSCW.
80 Verlicchi et al. (2013) stated the similar results for the relationship between the removal
81 efficiency of PhCs and Log Kow in HFCW. These studies indicated a non-substantial role of
82 hydrophobicity in the removal processes of PhCs in CWs. However, it was not fully clear
83 from the available studies why Log Kow does not yield a significant correlation with the
84 removal efficiencies like Log Dow, despite the fact that both are closely related and Log Dow
85 could be estimated using Log Kow (e.g., Carballa et al., 2008). Although Zhang et al. (2012b)
86 suggested that the removal efficiency of the selected PhCs can be predicted adequately in
87 HFCW based on their Log Dow, Verlicchi et al. (2013) suggested that Log Kow alone is not a
88 useful predictor for the behavior of PhCs in HFCW. These results indicate the potential role
89 of multiple physicochemical properties in their removal processes. However, the previous
90 research did not investigate the possibility of predicting the removal efficiency by combining
91 two or more physicochemical properties, i.e., multiple linear regression analysis to develop
92 predictive models for the removal efficiency with two or more physicochemical properties
93 was not conducted by the above-mentioned studies.

94 While most of the studies attempted to predict the removal efficiency of PhCs based on only
95 one physicochemical property (Log Kow and/or Log Dow), a study by Matamoros et al.
96 (2017) performed a correlation analysis between the removal efficiency of 16 EOCs including
97 PhCs, PCPs, and industrial chemicals and their corresponding values of Log Kow, HC, WS,
98 and MW. This study revealed a significant positive correlation of the removal efficiency with

99 Log Kow and MW. Nevertheless, the authors suggested a cautious interpretation of these
100 results, and stated that differences in their findings compared to earlier studies could be due to
101 the variability in the studied EOCs, weather conditions, sample size, and CW systems.
102 Vystavna et al. (2017) conducted a principle component analysis (PCA) to investigate the role
103 of physicochemical properties (WS, MW, and Log Kow) in the removal efficiency of 12
104 EOCs including PhCs, PCPs, and SHs in a hybrid constructed wetland (HCW). The results of
105 PCA suggested a non-significant relationship between the physicochemical properties of the
106 studied EOCs and their removal efficiency. The authors recommended a further analysis for
107 the confirmation of their findings.

108 The CW models can provide a very useful information for scientific understanding of the
109 processes and aiding in the design of the CWs (Meyer et al., 2015). However, existing models
110 of CWs, both process-based or black-box types, only focus on the removal of conventional
111 parameters such as nutrients, biochemical oxygen demand, and chemical oxygen demand
112 (e.g., Kumar and Zhao, 2011; Meyer et al., 2015; Yuan et al., 2020). In general, there is a
113 need to include EOCs in the further development of CW models (Yuan et al., 2020).
114 Furthermore, there is a need to carry out a comprehensive statistical analysis to develop
115 predictive models for the removal efficiency of EOCs (PhCs, PCPs, and SHs) based on their
116 physicochemical properties. Further research is required on investigating the combined impact
117 of several physicochemical properties (MW, WS, Log Kow, Log Koc, Log Dow, HC, and
118 pKa) to predict the removal prospects of EOCs in CWs, while giving attention to the
119 prediction of PCPs and SHs along with PhCs. The progress on predictive models will also
120 advance scientific understanding and contribute to improve the decision-making process. For
121 example, engineers and policy makers could readily use these models to obtain a first-hand
122 information on the expected removal efficiency of a certain PhC, PCP or SH in CWs. Such
123 information can be very valuable in data limited situations when no or a very limited

124 information on the removal efficiency of certain EOCs is available based on the field
125 research, which could be quite costly. Moreover, the new models can help in the further
126 development of modelling and decision support tools (DSTs) on EOCs.

127 Therefore, the main objective of this study is to comprehensively analyze the possibility of
128 developing reliable predictive models for the removal efficiency of EOCs in CWs based on
129 their physicochemical properties. The specific objectives are: (1) to explore the possibility of
130 developing statistical models for the prediction of removal efficiencies of individual group of
131 EOCs (PhCs, PCPs, and SHs) in CWs based on their physicochemical properties; (2) to
132 explore the possibility of formulating a generic predictive model by combining the removal
133 efficiencies of PhCs, PCPs, and SHs in CWs based on their physicochemical properties; (3) to
134 examine the impact of physicochemical properties of EOCs on their removal mechanisms in
135 CWs; (4) to study the inherent uncertainties involved in the development of the above-
136 mentioned predictive models; and (5) to explore the possibilities of application of the
137 plausible predictive models.

138 **2. Methodology**


139 **2.1. Data**

140 The flowchart of the research methodology is presented in Figure 1 and discussed below.
141 Predictive models were formulated using data of widely studied EOCs (PhCs: 33; PCPs: 15;
142 and SHs: 11) in CWs. The data was compiled from the peer-reviewed published sources in
143 our previous work (Ilyas et al., 2020; Ilyas and van Hullebusch, 2020c, 2020d), and formed
144 the basis of this modelling study. The removal efficiency is used as a dependent variable to be
145 predicted. The independent variables were physicochemical properties: HC, WS, MW, Log
146 Kow, Log Dow, Log Koc, and pKa. The data of these variables was collected from various
147 sources: quantitative structure activity relationship-QSAR Toolbox (version 4.3.1), journal

148 papers, reports, and websites. Despite some differences in the data values, these sources were
149 considered very useful and reliable. For example, the QSAR Toolbox contains data from
150 several reliable sources, and was very helpful in collecting the data of most of the variables.
151 However, data of Log Dow was not available for all the EOCs, and the missing values were
152 filled by developing regression equations of Log Dow with Log Koc (for PhCs) and Log Kow
153 (for PCPs). In the case of SHs, Log Kow values were used in place of Log Dow because the
154 studied compounds were neutral (e.g., Carballa et al., 2008), and regression analysis was not
155 possible due to a very limited number of data points for Log Dow. The final data sets used in
156 this study are given in Supplementary materials 2: Tables S2-S4.

157 **2.2. Statistical methods**

158 First, PCA was performed in R software (version 3.6.2). The PCA was mainly aimed at
159 understanding the role of different physicochemical properties in the removal processes.
160 Moreover, the PCA helped to understand the key variables explaining most of the variance in
161 the data set, and thus could be used in the model building process (Supplementary materials 3
162 and 4: Figures S1-S5 and Tables S5-S12). Second, a correlation of the removal efficiency of
163 EOCs and their physicochemical properties was estimated to select the most promising
164 variables to be used in the predictive models. Microsoft Excel software (Analysis ToolPak)
165 was used to estimate the Pearson product moment correlation (Supplementary materials 5:
166 Tables S13-S20).



167

168 Figure 1. Flowchart of the research methodology.

169 Note: Emerging organic contaminants (EOCs); Pharmaceuticals (PhCs); Personal care products (PCPs);

170 Steroidal hormones (SHs); Henry's Law Constant (HC); Water solubility (WS); Molecular weight (MW);

171 Octanol-water partition coefficient (Log Kow); Soil organic carbon sorption coefficient (Log Koc); Octanol-

172 water distribution coefficient (Log Dow); Dissociation constant (pKa).

173 Then, multiple linear regression analysis was carried out using Microsoft Excel software
174 (Analysis ToolPak) (Supplementary materials 6: Tables S21-S27). The available EOCs' data
175 sets were divided into the training and test sets using a purposive sampling approach based on
176 the number of data points in the case of removal efficiency of EOCs (Tables S2-S4). For
177 example, the data of PhCs with > 15 data points were used as one set in the model
178 formulation processes. Other sets included PhCs with > 20 and ≥ 25 data points, respectively.
179 It was assumed that more data points may reduce the uncertainty in the observed removal
180 efficiency and, therefore, may results in the development of better models (Supplementary
181 materials 7: Tables S28-S32). In the calibration process, various combinations of independent
182 variables were used to formulate multiple linear regressions. For example, the removal
183 efficiency was estimated using Log K_{oc} and Log D_{ow} in one model. Then, other variables
184 (e.g., MW and pK_a) were added into the model. The regressions models with $p \leq 0.1$ and R²:
185 > 0.60 were considered as satisfactory, and were selected for validation on an independent
186 data (test set) (Tables S2-S4). The difference between the observed and predicted removal
187 efficiency was used as an indicator to assess the performance of the regression models. Since
188 these differences were both positive and negative, it was not suitable to estimate the overall
189 mean difference because of the cancelling effect. Therefore, model performance was also
190 assessed using root mean square error (RMSE), which was estimated from the observed and
191 predicted removal efficiency. First, the regression models were developed separately for each
192 category of the EOCs. For example, the removal efficiency of PhCs was predicted using the
193 physicochemical properties of the examined PhCs. Similar approach was followed for PCPs
194 and SHs. Then, an attempt was made to form the models by combining data of different
195 EOCs. For example, the data of PhCs and PCPs was combined, and used to develop a
196 predictive model that could represent both categories of these EOCs. In a similar way,
197 combined models were developed for PhCs and SHs, PCPs and SHs, and PhCs, PCPs, and

198 SHs. The multiple linear regression approach was used for developing the individual as well
199 as generic models.

200 A novel DST, named as REOCW-PCP was developed for the potential application of the
201 predictive models formulated for predicting the removal efficiency of EOCs based on their
202 physicochemical properties. REOCW-PCP was developed using Microsoft Excel 2016, and is
203 provided as a supplementary material (Excel file: REOCW-PCP-secure, along with the user
204 manual).

205 **3. Results and Discussion**

206 **3.1. Predictive models for PhCs**


207 The first three principle components (PCs) with eigenvalue > 1.0 explained 71% of the
208 variance in the data of 33 widely studied PhCs (Figure 2 and Table 1). The first two PCs
209 could explain 56% of the variance in the data (PC1: 39%; PC2: 17%). In PC1, the high
210 positive loadings were observed for Log Koc, Log Kow, and Log Dow, and these variables
211 cluster together (Figure 3). In PC2, pKa and MW indicated high positive loadings and cluster
212 together (Figure 3 and Table 1). The removal efficiency indicated negative loadings in all
213 three PCs. Although the variance explained by the first three PCs is not very high, the results
214 show reasonably good prospects of establishing a relationship between the removal efficiency
215 and physicochemical properties of PhCs. To further test the reliability of the PCA results, we
216 also conducted PCA based on various combinations of the studied PhCs, i.e., samples with
217 number of data points > 15 , > 20 , and ≥ 25 . In general, the PCA results gave similar insights
218 as obtained using 33 PhCs (Figures S1-S3 and Tables S5-S8). This reveals that processes
219 behind the resulting models will follow a coherent pattern in all the combinations of selected
220 PhCs. For example, Log Koc is likely to emerge as an important predictor in all the cases, and

221 is likely to show a significant negative correlation with the removal efficiency of PhCs
 222 (Figure 4 and Tables S13-S16).


223 Table 1. Principle component analysis (PCA) results based on widely studied 33 PhCs, 15 PCPs, and
 224 11 SHs.

Description	PhCs			PCPs		SHs	
	PC1	PC2	PC3	PC1	PC2	PC1	PC2
Eigenvalue	1.758	1.162	1.120	2.109	1.236	1.971	1.574
Proportion of Variance	0.387	0.169	0.157	0.556	0.191	0.486	0.310
Cumulative Proportion	0.387	0.555	0.712	0.556	0.747	0.486	0.795
Variables and loadings							
HC (atm m ³ mol ⁻¹)	0.151	-0.639	-0.036	0.196	-0.558	0.139	0.415
WS (mg L ⁻¹)	-0.373	-0.062	0.355	-0.344	-0.066	-0.351	-0.395
MW (g mol ⁻¹)	0.042	0.469	-0.660	0.246	0.486	-0.364	0.247
Log Kow	0.498	-0.094	-0.259	0.466	-0.076	0.470	-0.071
Log Koc	0.491	-0.154	0.240	0.458	0.002	0.467	0.216
Log Dow	0.479	0.099	0.136	0.461	-0.093	0.473	-0.104
pKa	0.071	0.499	0.491	0.184	0.623	-0.014	0.574
RE (%)	-0.336	-0.277	-0.230	0.330	-0.212	-0.249	0.468

225 Note: Pharmaceuticals (PhCs); Personal care products (PCPs); Steroidal hormones (SHs); Principle component
 226 (PC); Henry's Law Constant (HC); Water solubility (WS); Molecular weight (MW); Octanol-water partition
 227 coefficient (Log Kow); Soil organic carbon sorption coefficient (Log Koc); Octanol-water distribution
 228 coefficient (Log Dow); Dissociation constant (pKa); Removal efficiency (RE).



229 Figure 2. Scree plot indicated the variance explained by each principle component (PC) for the data of
 230 widely studied 33 PhCs; 15 PCPs; and 11 SHs.
 231



232


233 Figure 3. Biplot of PC1 and PC2 based on principle component analysis (PCA) of 33 widely studied
 234 PhCs.

235 Note: Removal efficiency (RE); Diclofenac (1); Ibuprofen (2); Ketoprofen (3); Naproxen (4); Salicylic acid (5);
 236 Acetaminophen (6); Codeine (7); Tramadol (8); Clarithromycin (9); Doxycycline (10); Erythromycin (11);
 237 Ofloxacin (12); Oxytetracycline (13); Sulfadiazine (14); Sulfamethazine (15); Sulfamethoxazole (16);
 238 Sulfapyridine (17); Trimethoprim (18); Monensin (19); Fexofenadine (20); Caffeine (21); Diltiazem (22);
 239 Carbamazepine (23); Mirtazapin (24); Venlafaxine (25); Atenolol (26); Metoprolol (27); Sotalol (28); Ranitidine
 240 (29); Bezafibrate (30); Clofibrac acid (31); Gemfibrozil (32); and Furosemide (33).

241 The correlation and regression outcomes were quite consistent with the PCA results (Tables
 242 S5-S8, S13-S16, and S28). The best models were formed by combining Log Koc, Log Dow,
 243 Log Kow, MW, and pKa, mostly with three or four variables together in one model. The
 244 models with one or two variables were not acceptable ($R^2: < 0.50$; $p > 0.1$). This finding is
 245 consistent with Verlicchi et al. (2013) who also suggested that Log Kow alone is not a useful

246 predictor for the behavior of PhCs in CWs. On the other hand, these results are in contrast
 247 with the study of Zhang et al. (2018) which indicated the possibility of good prediction of the
 248 removal efficiency only with Log Dow based on high negative correlation between the two
 249 variables. Nevertheless, our results suggested that Log Dow is an important predictor when
 250 used along with other physicochemical properties.

251 Furthermore, a negative correlation of MW, Log Dow, Low Kow, and Log Koc with the
 252 removal efficiencies of PhCs suggested that the PhCs with high values of any of these
 253 physicochemical properties might lead to a low removal efficiency in CWs (Tables S13-S16).
 254 For example, this might be the reason of the low removal efficiency in the case of diclofenac,
 255 erythromycin, clarithromycin, fexofenadine, mirtazapin, carbamazepine, bezafibrate, and
 256 gemfibrozil in CWs (Table S2). In general, the PhCs which are readily biodegradable shows
 257 much better removal efficiencies in CWs (e.g., Hijosa-Valsero et al., 2010; Reyes-Contreras
 258 et al. 2012; Chen et al., 2016). In most of the cases, highly biodegradable PhCs have low
 259 values of Log Koc, Log Dow, Log Kow, and MW, which explains good prospects of their
 260 removal by CWs as substantiated by the statistical analysis conducted in this study.



261
 262 Figure 4. Pearson correlation statistics among the studied physicochemical properties and the removal
 263 efficiency of widely studied 33 PhCs, 15 PCPs, and 11 SHs.


264 Note: 'a' shows a significant correlation between the parameters at 95% confidence level. The number of data
265 points per pair was 33, 15, and 11 in the case of PhCs, PCPs, and SHs, respectively.

266 For acceptable models with $R^2: > 0.60$ and $p < 0.05$, the RMSEs in training set were $< 15\%$ in
267 all the cases (Table S28). In general, the difference in the observed and predicted removal
268 efficiency in the test set was quite good for most of the PhCs. For example, the difference in
269 the observed and predicted removal efficiency was $< 20\%$ in the case of 13 out of 18 PhCs
270 (72% of the cases) for the model formed based on MW, Log Dow, and Log Koc (Table S21).
271 The differences were even $< 10\%$ for half of the cases indicating very high level of accuracy
272 in predication in the case of venlafaxine, ofloxacin, codeine, mirtazapin, bezafibrate,
273 oxytetracycline, tramadol, and atenolol (Figure 5). However, three PhCs (monensin, sotalol,
274 and diltiazem) were not well predicted, as the difference in the removal efficiency was quite
275 high (ranging from 43% to 76%).

276 The performance of the plausible models is quite similar, as the RMSE values were around
277 30% with small differences among different models (e.g., $< 5\%$) (Table S28). This implies
278 that any of these models could be used for predictions, depending upon the availability of data
279 on physicochemical properties. However, acceptable models were further screened to
280 facilitate the selection of the best model for application. The model given in Equation 1 is
281 selected as the first choice, which is based on MW, Log Dow, and Log Koc (Tables S21 and
282 S28). This model was formulated using a training set of 15 PhCs with ≥ 25 data points, and it
283 was validated on an independent test set of 18 PhCs (Figure 5 and Table S2). The predicted
284 removal efficiency was quite good for most of the PhCs, and the overall RMSE of 27% was
285 the lowest compared with other models (Table S28).

$$286 \quad RE = 108.667 - 0.084 MW - 4.126 \text{ Log Dow} - 18.081 \text{ Log Koc} \quad (1)$$

287 Where, RE is removal efficiency in %; *MW* is molecular weight in g mol^{-1} ; *Log Dow* is
 288 octanol- water distribution coefficient; and *Log Koc* is soil organic carbon sorption
 289 coefficient.




290
 291 Figure 5. Difference between the observed and predicted removal efficiency based on the best model
 292 for PhCs with *MW*, *Log Dow*, and *Log Koc*.

293 3.2. Predictive models for PCPs

294 The first two PCs had eigenvalue > 1.0 and together could explain 75% of the variance in
 295 PCPs data (Figure 2 and Table 1). More details on PCA results with other combination of the
 296 studied PCPs are given in supplementary materials (Figure S4 and Tables S9 & S10). The
 297 first two PCs explained more variance in the case of PCPs compared with PhCs (75% VS
 298 56%) (Table 1), which illustrates better prospects of predictions in the case of PCPs compared
 299 with PhCs. The PC1 alone explained 56% of the variance in the PCPs data, with the highest
 300 positive loadings of *Log Kow*, *Log Dow*, and *Log Koc*, whereas, *pKa* and *MW* had highest
 301 positive loadings in PC2 (Figure 6 and Table 1). These loading results were similar to those

302 obtained for PhCs. However, the removal efficiency showed positive loading in the case of
 303 PCPs compared with negative loadings for PhCs (Table 1). This could be due to the
 304 differences between PhCs and PCPs in dominant removal mechanisms and the contribution of
 305 respective physicochemical properties to the removal processes. For instance, adsorption to
 306 the substrate and/or sorption onto organic surfaces is the dominant removal mechanism in
 307 most of the widely studied PCPs (e.g., Vymazal et al., 2017; Wang et al., 2019; Ilyas and van
 308 Hullebusch, 2020c). This explains a significant positive correlation of Log Kow, Log Dow,
 309 and Log Koc with the removal efficiency of PCPs (Figure 4 and Tables S17 & S18).



310

311 Figure 6. Byplot of PC1 and PC2 based on PCA of 15 widely studied PCPs.

312 Note: Acesulfame (1); Methylparaben (2); Propylparaben (3); N,N-diethyl-meta-toluamide (4); Triclosan (5);

313 Triclocarban (6); Methyl dihydro-jasmonate (7); Cashmeran (8); Galaxolide (9); Tonalide (10); Tributyl

314 phosphate (11); Triphenyl phosphate (12); Tris (2-chloroethyl) phosphate (13); Oxybenzone (14); and
315 Sulisobenzone (15).

316 The removal efficiency indicated a significant positive correlation with Log Dow, Log Koc,
317 and Log Kow, which was consistent with the PCA results (Figure 4 and Table 1). The
318 multiple linear regression models were formed using data of the training set of eight PCPs
319 with > 5 data points and was tested to predict the removal efficiency of seven PCPs (Table
320 S3). The RMSE values of the two promising models ($R^2 > 0.60$; $p \leq 0.1$) for the test set were
321 14% and 21% (Table S29). The model given in Equation 2 is selected as the best performing
322 model, which was based on two variables: Log Koc and Log Kow (Table S22), and resulted
323 in 14% RMSE in the test set.

$$324 \quad RE = 66.292 + 21.880 \text{ Log Kow} - 30.505 \text{ Log Koc} \quad (2)$$

325 Where, RE is removal efficiency in %; Log Kow is octanol-water partition coefficient; and
326 Log Koc is soil organic carbon sorption coefficient.


327 The addition of MW along with Log Kow and pKa resulted in the second-best model (Table
328 S23) with RMSE of 21% in the case of test set. The model is presented in Equation 3.

$$329 \quad RE = 49.970 - 0.056 \text{ MW} + 8.710 \text{ Log Kow} - 1.605 \text{ pKa} \quad (3)$$

330 Where, RE is removal efficiency in %; MW is molecular weight in g mol^{-1} ; Log Kow is
331 octanol-water partition coefficient; and pKa is dissociation constant.

332 In most of the cases, the difference in the observed and predicted removal efficiency was
333 small in both models, as illustrated for the best model by Figure 7. The difference in the
334 observed and predicted removal efficiency was < 10% in the case of five out of seven tested
335 PCPs (cashmeran, triclocarban, triphenyl phosphate, N,N-diethyl-meta-toluamide, and tributyl
336 phosphate). Furthermore, a significant positive correlation of Log Kow, Log Koc, and Log

337 Dow with the removal efficiencies of PCPs suggested that the PCPs with high values of any
 338 of these physicochemical properties might lead to a high removal efficiency in CWs (Tables
 339 S17 and S18). This might be the reason of the moderate to high removal efficiency of most of
 340 the studied PCPs with the exception of tributyl phosphate and propylparaben in CWs (Table
 341 S3).




342

343 Figure 7. Difference between the observed and predicted removal efficiency based on the best model
 344 for PCPs with Log Kow and Log Koc.

345 3.3. Predictive models for SHs

346 The first two PCs had eigenvalue > 1.0 and could explain 80% of the variance in the SHs data
 347 (PC1: 49%; PC2: 31%) (Figure 2 and Table 1). Like PhCs and PCPs, Log Dow, Log Kow,
 348 and Log Koc showed high positive loadings in PC1. For PC2, high positive loadings were
 349 shown by pKa, RE, and HC (Figure 8 and Table 1). More detail on PCA analysis is given in
 350 supplementary materials (Figure S5 and Tables S11 & S12). The correlation and regression
 351 results were consistent with the PCA results (Figure 4 and Tables S19 & S20), indicating the
 352 important role of these physicochemical properties in estimating the removal efficiencies of
 353 the SHs in CWs.



354

355 Figure 8. Byplot of PC1 and PC2 based on PCA of 11 widely studied SHs.

356 Note: 17α -ethinylestradiol (1); 17β -estradiol (2); Estrone (3); Estriol (4); Progesterone (5); Norethisterone (6);

357 Levonorgestrel (7); Androstenedione (8); Boldenone (9); Testosterone (10); and Prednisone (11).

358 The multiple linear regression models were formed using data of the training set of six SHs

359 with > 10 data points and was tested to predict the removal efficiency of five SHs (Table S4).

360 The resulting predictive models were very good ($R^2: \geq 0.90$; $p \leq 0.1$), and are given in Table

361 S30. The best model was formed by combining MW, Log Kow, and pKa (Table S24), and

362 yielded quite good performance for the training set (RMSE: 3%) and the test set (RMSE:

363 15%) (Equation 4). Three out of five tested SHs (boldenone, norethisterone, and


364 progesterone) had very less difference in the observed and predicted removal efficiency (<

365 10%) (Figure 9). The difference in the case of other two SHs (prednisone and

366 androstenedione) was 17% and 27%, respectively.

367
$$RE = 58.032 - 0.035 MW - 7.244 \text{ Log } Kow + 3.863 pKa \quad (4)$$

368 Where, *RE* is removal efficiency in %; *MW* is molecular weight in g mol⁻¹; *Log Kow* is
 369 octanol-water partition coefficient; and *pKa* is dissociation constant.



370

371 Figure 9. Difference between the observed and predicted removal efficiency based on the best model
 372 for SHs with MW, Log Kow, and pKa.

373 3.4. Predictive models for EOCs combining PhCs, PCPs, and SHs

374 3.4.1. Predictive models combining PhCs and PCPs

375 PCA results showed that removal efficiency has negative loadings for PhCs and does not
 376 cluster with Log Kow, Log Koc, and Log Dow, which have high positive loadings in PC1
 377 (Figure 3 and Table 1). In contrast, the removal efficiency cluster with Log Kow, Log Koc,
 378 and Log Dow in the case of PCPs (Figure 6 and Table 1), and these variables indicated
 379 positive loadings in PC1. Due to these differences, the correlation and multiple linear
 380 regression models were not acceptable for the training set. For example, R² was very low (<
 381 0.25), and the regression models were not statistically significant (*p* > 0.1). Thus, these
 382 models were not suitable for the validation step.

383 This lack of adequate predictive power of the combined model of PhCs and PCPs could be
384 attributed to the distinct differences in the physicochemical properties of these compounds as
385 well as differences in the dominant removal mechanisms in the CWs. For example,
386 biodegradation (aerobic and/or anaerobic) is the most dominant removal mechanism for PhCs
387 removal (e.g., Choi et al., 2016; Nivala et al., 2019; Ilyas et al., 2020). On the other hand,
388 PCPs have adsorption to the substrate and sorption onto organic surfaces as their major
389 removal mechanisms (e.g., Carranza-Diaz et al., 2014; Matamoros et al., 2016; Ilyas and van
390 Hullebusch, 2020c). Most of the PCPs have higher Log Kow, Log Dow, and Log Koc values
391 and low water solubility compared with PhCs (Tables S2 and S3). On the other hand,
392 Matamoros et al. (2017) reported a significant positive correlation ($p < 0.05$) of the removal
393 efficiency of the combined PhCs and PCPs with Log Kow. However, the studied PhCs
394 (diclofenac, naproxen, ibuprofen, ketoprofen, and carbamazepine) has moderate to high Log
395 Kow which is comparable with the Log Kow of the studied PCPs (tributyl phosphate,
396 triphenyl phosphate, tris (2-chloroethyl) phosphate, galaxolide, tonalide, oxybenzone, methyl
397 dihydro-jasmonate, triclosan, and methyl paraben) (Tables S2 and S3).

398 **3.4.2. Predictive models combining PhCs and SHs**

399 PCA results showed that removal efficiency has negative loadings for both PhCs and SHs in
400 PC1 and does not cluster with Log Kow, Log Koc, and Log Dow which have high positive
401 loadings (Figures 3 & 8 and Table 1). The consistency in PCA and correlation results (Figure
402 4 and Table 1) contributed in forming acceptable predictive models with the combined data of
403 PhCs and SHs (Tables S25 and S31). This adequate predictive power of the combined models
404 might be due to the similarities in the physicochemical properties of these compounds (Tables
405 S2 and S4), as well as correspondence in their dominant removal mechanisms in the CWs. For
406 example, the biodegradation (aerobic and/or anaerobic) is the most dominant removal


407 mechanism for PhCs and SHs removal (e.g., Herrera-Melián et al., 2018; Chen et al., 2019;
408 Ilyas et al., 2020; Ilyas and van Hullebusch, 2020d).

409 The models were formed by combining Log K_{oc}, Log K_{ow}, Log D_{ow}, MW, and pK_a, mostly
410 with three or four variables together in one model. Although R² was not high (only about 0.4),
411 the regression models were statistically significant at 95% or 90% confidence interval ($p \leq$
412 0.1) (Table S31). Therefore, the resulting regression statistics were acceptable for the training
413 set and were applied on the test set (Table S25). For acceptable models, the RMSEs in the
414 training set were 15% in all the cases.

415 The best model was formed by combining MW, Log K_{ow}, Log K_{oc}, and pK_a (Equation 5),
416 and yielded satisfactory results for the test set (RMSE: 27%) (Table S31). The difference in
417 the observed and predicted removal efficiency of 17 out of 23 tested PhCs and SHs was \leq
418 25%. The difference in the observed and predicted removal efficiency was quite small (<
419 10%) in the case of codeine, atenolol, ranitidine, bezafibrate, androstenedione, and
420 gemfibrozil (Figure 10). However, six out of 23 PhCs and SHs had a quite high difference in
421 the observed and predicted removal efficiency (ranging from 30% to 60%).

$$422 \quad RE = 75.093 - 0.094 MW + 4.249 \text{ Log } K_{ow} - 11.878 \text{ Log } K_{oc} + 2.541 pKa \quad (5)$$

423 Where, *RE* is removal efficiency in %; *MW* is molecular weight g mol⁻¹; *Log K_{ow}* is octanol-
424 water partition coefficient; *Log K_{oc}* is soil organic carbon sorption coefficient; and *pK_a* is
425 dissociation constant.



426

427 Figure 10. Difference between the observed and predicted removal efficiency based on the best model
 428 for combined PhCs and SHs with MW, Log Kow, Log Koc, and pKa.

429 3.4.3. Predictive models combining PCPs and SHs

430 In the case of PCPs and SHs, the models were formed by combining Log Koc, Log Kow, Log
 431 Dow, and MW, mostly with two or more variables together in one model. Although R^2 was
 432 not very high (about 0.5), the regression models were statistically significant at 95% or 90%
 433 confidence interval in most of the cases ($p < 0.1$) (Table S32). Therefore, the resulting
 434 regression statistics were acceptable (Table S26). For acceptable models, the RMSEs in the
 435 training set were 15% or 16%. The difference in the observed and predicted removal
 436 efficiency was not very large for most of the models, as illustrated by the results of the best
 437 model (Figure 11). The best performing model was formed by combining MW, Log Dow, and
 438 Log Koc (Equation 6), which yielded quite good results for both the training set (RMSE:
 439 15%) and the test set (RMSE: 23%) (Table S32). The difference in the observed and predicted
 440 removal efficiency of seven out of 14 PCPs and SHs was $< 20\%$. Two compounds
 441 (propylparaben and boldenone) showed difference in the observed and predicted removal
 442 efficiency up to 29%. The difference in the observed and predicted removal efficiency was

443 small (< 15%) in the case of cashmeran, triphenyl phosphate, triclocarban, N,N-diethyl-meta-
444 toluamide, tributyl phosphate, and androstenedione (Figure 11). This indicate that the removal
445 efficiency of these compounds could be adequately predicted by the proposed models.
446 However, in the case of three compounds (progesterone, norethisterone, and prednisone) the
447 difference in the observed and predicted removal efficiency was high (> 30%).

$$448 \quad RE = 48.691 + 0.049 MW + 15.545 \text{ Log } Dow - 18.451 \text{ Log } Koc \quad (6)$$


449 Where, *RE* is removal efficiency in %; *MW* is molecular weight g mol⁻¹; *Log Kow* is octanol-
450 water distribution coefficient; and *Log Koc* is soil organic carbon sorption coefficient.

451 The second-best model presented in Equation 7 is also possible with *MW*, *Log Kow*, and *Log*
452 *Koc* (Table S27), which yielded almost similar results for the training and test sets (RMSEs:
453 16% and 24%, respectively) (Table S32). However, this model was not able to explain more
454 variance compared with the best model. Nevertheless, the differences in observed and pre-
455 dicted removal efficiencies were somewhat similar to the best model.

$$456 \quad RE = 39.301 + 0.098 MW + 15.363 \text{ Log } Kow - 20.475 \text{ Log } Koc \quad (7)$$

457 Where, *RE* is removal efficiency in %; *MW* is molecular weight g mol⁻¹; *Log Kow* is octanol-
458 water distribution coefficient; and *Log Koc* is soil organic carbon sorption coefficient.

459 The adequate predictive power of the combined model of PCPs and SHs might be due to the
460 similarities in some of the physicochemical properties of these compounds in most of the
461 cases (e.g., high *Log Koc* > 2.50 and low *WS* < 500) (Tables S3 and S4).



462

463 Figure 11. Difference between the observed and predicted removal efficiency based on the best model
 464 for combined PCPs and SHs with MW, Log Dow, and Log Koc.

465 3.4.4. Predictive models combining PhCs, PCPs, and SHs

466 The performance of combined models with PhCs, PCPs and SHs was not satisfactory, as
 467 demonstrated by weak correlations and multiple linear regression results. For example, the
 468 resulting regression statistics were not acceptable for the training set because R^2 was very low
 469 (< 0.3) and the regression models were not statistically significant ($p > 0.1$). Thus, these
 470 models were not tested to predict the removal efficiency of the combined data of PhCs, PCPs,
 471 and SHs.

472 This lack of adequate predictive power of the combined model could be attributed to the
 473 distinct differences in the physicochemical properties of these compounds, in particular PhCs
 474 and PCPs, as well as the differences in their dominant removal mechanisms in CWs. For
 475 example, the biodegradation (aerobic and/or anaerobic) is the most dominant removal
 476 mechanism for PhCs and SHs in CWs (e.g., Rühmland et al., 2015; Dai et al., 2017; Ilyas et
 477 al., 2020; Ilyas and van Hullebusch, 2020d). The satisfactory predictive power of the
 478 combined model of PhCs and SHs might be due to the similarities in some of the

479 physicochemical properties of these compounds (e.g., Log Kow, Log Dow, and Log Koc) in
480 most of the cases (Tables S2 and S4). On the other hand, PCPs have adsorption to the
481 substrate and/or sorption onto organic surfaces as their major removal mechanisms (e.g.,
482 Matamoros et al., 2016; Vystavna et al., 2017; Ilyas and van Hullebusch, 2020c). Most of the
483 PCPs have much higher Log Kow, Log Dow, and Log Koc values and low WS compared
484 with PhCs (Tables S2 and S3). The adequate predictive power of the combined model of
485 PCPs and SHs might be due to the similarities in some of the physicochemical properties of
486 these compounds (e.g., high Log Koc > 2.50 and low WS < 500) in most of the cases (Tables
487 S3 and S4). These distinct features in their physicochemical properties lead to the differences
488 in their dominant removal mechanisms and hinder the possibility to formulate a generic
489 predictive model based on a combined data set of PhCs, PCPs, and SHs. These findings are
490 consistent with the study by Vystavna et al. (2017). The authors reported no correlation
491 among the physicochemical properties (WS, MW, and Log Kow) of PhCs, PCPs, and SHs
492 with their removal efficiencies in CWs based on the PCA results.

493 **3.5. Uncertainty Analysis**


494 The removal efficiencies of PhCs, PCPs, and SHs could be predicted at variable degree of
495 accuracy by using the proposed models. Although few models with combined data sets (e.g.,
496 PhCs and SHs; PCPs and SHs) indicated satisfactory performance, the predictions with
497 individual models for PhCs, PCPs, and SHs were more reliable. However, there is some
498 degree of uncertainty in the outcomes of all the predictive models, which could be considered
499 in the analysis and the decision-making process. One way to include the uncertainty in the
500 results is to make the predictions using more than one acceptable model, and then including
501 the uncertainty range in the outcome. Using this approach, mean and standard deviation of the
502 predicted removal efficiency of each PhCs, PCPs, and SHs was estimated using all the
503 acceptable models. Figure 12, illustrates this point with an example of predicted mean and

504 standard deviation of PhCs based on the five acceptable models. The prediction uncertainty
505 among different models was not very high because the standard deviations were quite small in
506 most of the cases (< 5%). The RMSE values estimated based on the average predicted
507 removal efficiency of all the models was 28%, which was not much different from that of the
508 individual models (Table S28).

509 Similar procedure was followed for PCPs and SHs, and combined models (PhCs and SHs;
510 PCPs and SHs), and the resulting uncertainty range of predictions in their removal efficiencies
511 are shown in Figures 13-16. The results follow similar pattern, with relatively small
512 uncertainty ranges for most of the EOCs. The RMSE values for average of more than one
513 model were also comparable to the best model. Therefore, it seems reasonably good to use
514 either the best model to have one deterministic prediction of the removal efficiency or
515 estimate mean and standard deviation based on all the promising models. The application of
516 the latter option could be preferred, as this approach is a good reminder that the predicted
517 values could not be taken as exact estimates and are always have some degree of uncertainty
518 attached to them.

519 Another source of uncertainty is related to the data of physicochemical properties and removal
520 efficiencies. For example, there could be some degree of uncertainty attached to the mean of
521 the observed removal efficiency (Tables S2-S4), and it is not possible to take these
522 observations as fully accurate measure of the central tendency. Furthermore, values of some
523 physicochemical properties like MW and WS have high degree of accuracy (less uncertainty).
524 Whereas, values of some other physicochemical properties like Log Dow could have a bit
525 higher degree of uncertainty because these were not easily available from the experimental
526 studies, and were estimated from other models.

527 Thus, the predicated removal efficiencies should be interpreted with caution. These
528 predictions could not be taken as absolute numbers; neither these should be considered as a
529 substitute for rigorous experimental studies.




530

531 Figure 12. Difference between the observed and predicted removal efficiency based on five acceptable models formed using data of 15 PhCs with ≥ 25 data
 532 points.

533 Note: Standard deviation values were capped at 100 to improve the readability of the graph. Actual values can be found in the developed decision support tool (DST),


534 REOCW-PCP provided as a supplementary material (Excel file: REOCW-PCP-secure, along with the user manual).



535

536 Figure 13. Difference between the observed and predicted removal efficiency based on two acceptable models formed using data of eight PCPs with > 5 data
 537 points.


538 Note: Standard deviation values were capped at 100 to improve the readability of the graph. Actual values can be found in the developed DST, REOCW-PCP.



539

540 Figure 14. Difference between the observed and predicted removal efficiency based on three acceptable models formed using data of six SHs with > 10 data
 541 points.


542 Note: Standard deviation values were capped at 100 to improve the readability of the graph. Actual values can be found in the developed DST, REOCW-PCP.



543

544 Figure 15. Difference between the observed and predicted removal efficiency based on one acceptable model formed using data of 15 PhCs and six SHs with
 545 data points ≥ 25 and > 10 , respectively.

546 Note: Standard deviation of the removal efficiency in the case of combined model of PhCs and SHs was not available because predictions are made based on one model.



547

548 Figure 16. Difference between the observed and predicted removal efficiency based on four acceptable models formed using data of eight PCPs and six SHs

549 with data points > 5 and > 10, respectively.


550 Note: Standard deviation values were capped at 100 to improve the readability of the graph. Actual values can be found in the developed DST, REOCW-PCP.

551 **4. Further development and applications**

552 The novel predictive models developed in this study could be useful DSTs. For example, the
553 plausible models could be used as screening tools to obtain first-hand information on the
554 removal efficiency of a certain PhC, PCP or SH when the wastewater containing them is
555 treated using CWs. The predicted removal efficiency can give an overview of mean as well as
556 range (e.g., standard deviation), providing insights into possible removal efficiency. This
557 information may guide in decision making on research directions as well as policy actions,
558 and practice (e.g., design and application of CWs in the field conditions).

559 Another area of application and further development could be to include these predictive
560 models into already existing DSTs. For example, the addition of the proposed models to
561 QSAR toolbox could extend its screening services to the domain of wastewater treatment
562 using CWs. The QSAR toolbox contains a wealth of information on a large number of
563 chemicals including PhCs, PCPs, and SHs, which may offer wider scale application of the
564 novel models developed in this study. The QSAR tool is widely used for various purposes,
565 most notably for the screening of new drugs based on existing QSAR in order to limit
566 experimental and clinical trials to save time, costs, and animal lives. In a similar way,
567 screening of a large number of PhCs, PCPs, and SHs could be possible when the models
568 developed in this study will become part of the QSAR toolbox.

569 Moreover, the predictive models could be used in developing new DSTs for researchers,
570 practitioners, policy makers, and citizens. For example, the authors have developed a novel
571 DST based on this research, which is named as REOCW-PCP. The key features of the DST
572 are schematized in Figure 17 and outlined below. REOCW-PCP was developed using
573 Microsoft Excel 2016, and is provided as a supplementary material (Excel file: REOCW-
574 PCP-secure, along with the user manual).



575

576 Figure 17. A schematic diagram showing different modules of the developed DST, REOCW-PCP.

577 The proposed REOCW-PCP is composed of seven modules, which could be followed
 578 sequentially. The first module displays the basic set up of REOCW-PCP, and contains the list
 579 of key questions that could be explored using the tool. REOCW-PCP can be used by an
 580 individual user or multiple users in the form of a group of different stakeholders (e.g.,
 581 policy/decision makers, wastewater managers, researchers/scientists, and citizens). The key
 582 questions are enumerated below.

583 **1.** What could be the removal efficiency of a certain EOC in CWs?

584 **2.** What is the likelihood of removal efficiency in falling under a certain quartile range (e.g.,
 585 Q1: 0-25%; Q2: 26-50%; Q3: 51-75%; Q4: 76-100%)?

586 **3.** Which physicochemical properties are better predictor of the removal efficiency for a
 587 certain EOC?

588 4. How the predicted and experimental removal efficiencies differ from each other?

589 5. What is the range of uncertainty in the available prediction and field observations?

590 6. What is the potential environmental risk posed by the EOCs of interest?

591 7. What lessons could be drawn based on the predictions and observations?

592 The second module contains the basic data of the EOCs including their names and
593 physicochemical properties. In this module, the user will select specific EOCs to examine. In
594 case REOCW-PCP is used by multiple stakeholders, they need to agree on the final list of the
595 EOCs to be examined. After selecting the EOCs from the given list, the tool automatically
596 does the required calculations to answer the key questions. The answers to these questions are
597 presented under module 7, and are ready for the review. However, it is recommended that the
598 users go through all the modules (3-7) in a sequential way to develop a good understanding of
599 the predictive models, details on calculations, and some key information provided in each
600 module.

601 The third module is composed of the novel predictive models developed in this research.
602 These models are used to make prediction of the removal efficiency, and used in making the
603 calculations required to answer the questions indicated under module 1. The fourth module
604 displays the results of the predicted removal efficiencies. The results are shown as a
605 deterministic value in the case of a single model application (e.g., best model) or mean and
606 standard deviation (e.g., including uncertainty range) when multiple models are used. The
607 fifth module enables further analysis of the results, mainly by comparing the predicted and
608 observed removal efficiency. This will help to triangulate the predictions with experimental
609 results, which will contribute to informed decision-making process. We have included
610 information on environmental risk posed by the EOCs in the sixth module, which is based on
611 our previous work (Ilyas et al., 2020; Ilyas and van Hullebusch, 2020c, 2020d). The results

612 are classified under various risk categories: high, medium, low, and no risk. The seventh
613 module offers the possibility to the users of this tool to find the answers to the key questions
614 and then discuss the lessons, and conclusions that could be drawn from the study. In this
615 module, standard answers to the questions are generated in Tabular and Graphical forms,
616 which will contribute to kick-off the discussion. Finally, the users may choose to finish the
617 session or choose to repeat the whole cycle (all modules) or a part of it (e.g., specific
618 modules) using a new set of EOCs.

619 **5. Conclusions**

620 The following conclusions are drawn from this study:

621 **1.** The physicochemical properties of EOCs are good predictors of their removal efficiency
622 in CWs. This was demonstrated by developing several plausible predictive models formed
623 by combining two to four physicochemical properties (MW, Log Dow, Log Koc, Log
624 Kow, and pKa) in a multiple linear regression model. Among the studied physicochemical
625 properties, Log Koc, Log Dow, and Log Kow emerged as the most significant predictors,
626 and combination of one or two of them with MW and/or pKa often improved the
627 reliability of the predictions.

628 **2.** The removal efficiency of PhCs, PCPs, and SHs in CWs could be predicted reasonably
629 well using their physicochemical properties: MW, Log Dow, Log Koc, Log Kow, and
630 pKa. In the case of PhCs, several novel models were formed to predict their removal
631 efficiency by combining three or four of these variables together in one model and the best
632 model was formed by combining MW, Log Dow, and Log Koc (R^2 : 0.601; $p < 0.05$;
633 RMSEs: training set: 11%; test set: 27%). In the case of PCPs, the two plausible models
634 were developed, one with two independent variables: Log Kow and Log Koc (R^2 : 0.644; p
635 < 0.1 ; RMSEs: training set: 14%; test set: 14), and the other with MW, Log Kow, and pKa

636 (R^2 : 0.709 and $p \leq 0.1$; RMSEs: training set: 13%; test set: 21%). Similarly, the removal
637 efficiency of SHs could be predicted very well by combining three of the five
638 physicochemical properties and the reliability of the developed models was quite high, as
639 demonstrated by a very good performance statistics for the three plausible models (R^2 : \geq
640 0.90; $p \leq 0.1$; RMSEs: training set: 3-4%; test set: 15-19 %).

641 **3.** The resulting regression statistics of a generic model by combining PhCs, PCPs, and SHs
642 were not acceptable for the training set, as demonstrated by a very low performance
643 statistics (R^2 : < 0.3 ; p -values were much higher than 0.1). The lack of adequate predictive
644 power of the combined model could be attributed to the distinct differences in the
645 physicochemical properties of PhCs and PCPs as well as the differences in their dominant
646 removal mechanisms in CWs. For example, most of the PCPs have much higher Log
647 Kow, Log Dow, and Log Koc values and low WS compared with PhCs. Consequently,
648 biodegradation (aerobic and/or anaerobic) is the most dominant removal mechanism for
649 PhCs, and adsorption to the substrate and sorption onto organic surfaces for PCPs in CWs.
650 These distinct features in their physicochemical properties lead to the differences in their
651 dominant removal mechanisms and could limit the possibility to formulate a generic
652 predictive model based on a combined data set of PhCs, PCPs, and SHs.

653 **4.** The adequate predictive power of the combined model of PhCs and SHs was achieved,
654 which might be due to the similarities in some of the physicochemical properties of these
655 compounds (e.g., Log Kow, Log Dow, and Log Koc) in most of the cases. The best
656 performing model was formed by combining MW, Log Kow, Log Koc, and pKa, which
657 demonstrated a very good performance for the training set (RMSE: 3%) and the test set
658 (RMSE: 15%).

659 5. The combination of PCPs and SHs also resulted in reasonably good predictive models.
660 The adequate predictive power of the combined model of PCPs and SHs might be due to
661 the similarities in some of the physicochemical properties of these compounds (e.g., high
662 Log Koc > 2.50 and low WS < 500) in most of the cases. The best model was formed by
663 combining MW, Log Dow, and Log Koc, which yield quite good results for the training
664 set (RMSE: 15%) and the test set (RMSE: 23%).

665 6. It is very important to recognize the inherent uncertainties associated with the prediction
666 process. These uncertainties could be related to the input data (e.g., removal efficiencies
667 and physicochemical properties of EOCs) and the variability in the predictions made from
668 multiple plausible models. Therefore, these uncertainties should be recognized, and the
669 prediction results should be used with caution. It is advisable to estimate the mean and
670 standard deviation based on all the promising models, even though one estimate from the
671 best model could also serve the purpose. Where field data is available, a comparison with
672 observed values is advisable.

673 7. From the application point of view, the novel and plausible predictive models developed
674 in this study could be useful DSTs. In particular, the proposed models could serve as
675 screening tools to gain insights about the removal efficiency of a certain PhC, PCP or SH
676 in CWs. Moreover, the models could be included into existing DSTs such as inclusion
677 into the QSAR toolbox to extend its capabilities to offer the screening of EOCs removal
678 by CWs. There are good prospects to develop new DSTs using the predictive models
679 developed in this study. For example, a novel DST named as REOCW-PCP was
680 developed based on the findings of this research. In general, the information obtained by
681 the use of the proposed predictive models and developed REOCW-PCP could contribute
682 to enhance the knowledge and understanding for the design and application of CWs for
683 EOCs removal from the wastewater

684 References

- 685 Barbosa, M.O., Moreira, N.F.F., Ribeiro, A.R., Pereira, M.F.R., Silva, A.M.T., 2016. Occurrence and
686 removal of organic micropollutants: an overview of the watch list of EU Decision 2015/495.
687 *Water Res.* 94, 257-279. DOI: <https://doi.org/10.1016/j.watres.2016.02.047>
- 688 Breitholtz, M., Näslund, M., Stråe, D., Borg, H., Grabic, R., Fick, J., 2012. An evaluation of free water
689 surface wetlands as tertiary sewage water treatment of micro-pollutants. *Ecotoxicol. Environ.*
690 *Saf.* 78, 63-71. DOI: <https://doi.org/10.1016/j.ecoenv.2011.11.014>
- 691 Caliman, F.A., Gavrilesco, M., 2009. Pharmaceuticals, personal care products and endocrine
692 disrupting agents in the environment-a review. *Clean* 37 (4-5), 277-303.
693 DOI: <https://doi.org/10.1002/clen.200900038>
- 694 Carballa, M., Fink, G., Omil, F., Lema, J.M., Ternes, T., 2008. Determination of the solid-water
695 distribution coefficient (Kd) for pharmaceuticals, estrogens and musk fragrances in digested
696 sludge. *Water Res.* 287-295. DOI: <https://doi.org/10.1016/j.watres.2007.07.012>
- 697 Carranza-Diaz, O., Schultze-Nobre, L., Moeder, M., Nivala, J., Kusch, P., Koeser, H., 2014.
698 Removal of selected organic micropollutants in planted and unplanted pilot-scale horizontal
699 flow constructed wetlands under conditions of high organic load. *Ecol. Eng.* 71, 234-245. DOI:
700 <https://doi.org/10.1016/j.ecoleng.2014.07.048>
- 701 Chen, J., Liu, Y.-S., Deng, W.-J., Ying, G.-G., 2019. Removal of steroid hormones and biocides from
702 rural wastewater by an integrated constructed wetland. *Sci. Total Environ.* 660, 358-365. DOI:
703 <https://doi.org/10.1016/j.scitotenv.2019.01.049>
- 704 Chen, Y., Vymazal, J., Březinová, T., Koželuh, M., Kule, L., Huang, J., Chen, Z., 2016. Occurrence,
705 removal and environmental risk assessment of pharmaceuticals and personal care products in
706 rural wastewater treatment wetlands. *Sci. Total Environ.* 566-567, 1660-1669. DOI:
707 <https://doi.org/10.1016/j.scitotenv.2016.06.069>
- 708 Choi, Y.-J., Kim, L.-H., Zoh, K.-D., 2016. Removal characteristics and mechanism of antibiotics using
709 constructed wetlands. *Ecol. Eng.* 91, 85-92. DOI: <https://doi.org/10.1016/j.ecoleng.2016.01.058>

710 Dai, Y., Tao, R., Tai, Y., Tam, N.F., Dan, A., Yang, Y., 2017. Application of a full-scale newly
711 developed stacked constructed wetland and an assembled bio-filter for reducing phenolic
712 endocrine disrupting chemicals from secondary effluent. *Ecol. Eng.* 99, 496-503. DOI:
713 <https://doi.org/10.1016/j.ecoleng.2016.11.007>

714 Gogoi, A., Mazumder, P., Tyagi, V.K., Chaminda, G.G.T., An, A.K., Kumar, M., 2018. Occurrence
715 and fate of emerging contaminants in water environment: a review. *Groundw. Sustain. Dev.* 6,
716 169-180. DOI: <https://doi.org/10.1016/j.gsd.2017.12.009>

717 Gorito, A.M., Ribeiro, A.R., Almeida, C.M.R., Silva, A.M.T., 2017. A review on the application of
718 constructed wetlands for the removal of priority substances and contaminants of emerging
719 concern listed in recently launched EU legislation. *Environ. Pollut.* 227, 428-443. DOI:
720 <https://doi.org/10.1016/j.envpol.2017.04.060>

721 Herrera-Melián, J.A., Guedes-Alonso, R., Borreguero-Fabelo, A., Santana-Rodríguez, J.J., Sosa-
722 Ferrera, Z., 2018. Study on the removal of hormones from domestic wastewaters with lab-scale
723 constructed wetlands with different substrates and flow directions. *Environ. Sci. Pollut. Res.* 25
724 (21), 20374-20384. DOI: <https://doi.org/10.1007/s11356-017-9307-8>

725 Hijosa-Valsero, M., Matamoros, V., Sidrach-Cardona, R., Martin-Villacorta, J., Becares, E., Bayona,
726 J.M., 2010. Comprehensive assessment of the design configuration of constructed wetlands for
727 the removal of pharmaceuticals and personal care products from urban wastewaters. *Water Res.*
728 44, 3669-3678. DOI: <https://doi.org/10.1016/j.watres.2010.04.022>

729 Ilyas, H., Masih, I., van Hullebusch, E.D., 2020. Pharmaceuticals removal by constructed wetlands: a
730 critical evaluation and meta-analysis on performance, risk reduction and role of
731 physicochemical properties on removal mechanisms. *J. Water Health* 18 (3), 253-291. DOI:
732 <https://doi.org/10.2166/wh.2020.213>

733 Ilyas, H., van Hullebusch, E.D., 2019. Role of design and operational factors in the removal of
734 pharmaceuticals by constructed wetlands. *Water* 11 (11), 2356, 1-24.
735 DOI: <https://doi.org/10.3390/w11112356>

736 Ilyas, H., van Hullebusch, E.D., 2020a. Performance comparison of different types of constructed
737 wetlands for the removal of pharmaceuticals and their transformation products: a review.

738 *Environ. Sci. Pollut. Res.* 27 (13), 14342–14364. DOI: [https://doi.org/10.1007/s11356-020-](https://doi.org/10.1007/s11356-020-08165-w)
739 [08165-w](https://doi.org/10.1007/s11356-020-08165-w)

740 Ilyas, H., van Hullebusch, E.D., 2020b. The influence of design and operational factors on the removal
741 of personal care products by constructed wetlands. *Water* 12 (5), 1367, 1-20. DOI:
742 <https://doi.org/10.3390/w12051367>

743 Ilyas, H., van Hullebusch, E.D., 2020c. Performance comparison of different constructed wetlands
744 designs for the removal of personal care products. *Int. J. Environ. Res. Public Health* 17 (9),
745 3091, 1-26. DOI: <https://doi.org/10.3390/ijerph17093091>

746 Ilyas, H., van Hullebusch, E.D., 2020d. A review on the occurrence, fate, and removal of steroidal
747 hormones during treatment with different types of constructed wetlands. *J. Environ. Chem. Eng.*
748 8 (3), 103793. DOI: <https://doi.org/10.1016/j.jece.2020.103793>

749 Kumar, J.L., Zhao, Y.Q., 2011. A review on numerous modeling approaches for effective, economical
750 and ecological treatment wetlands. *J. Environ. Manage.* 92, 400-406. DOI:
751 <https://doi.org/10.1016/j.jenvman.2010.11.012>

752 Lee, S., Kang, S.-I., Lim, J.-L., Huh, Y.J., Kim, K.-S., Cho, J., 2011. Evaluating controllability of
753 pharmaceuticals and metabolites in biologically engineered processes, using corresponding
754 octanol-water coefficient. *Ecol. Eng.* 37 (10), 1595-1600. DOI:
755 <https://doi.org/10.1016/j.ecoleng.2011.04.007>

756 Luo, Y., Guo, W., Ngo, H.H., Nghiem, L.D., Hai, F.I., Zhang, J., Liang, S., Wang, X.C., 2014. A
757 review on the occurrence of micropollutants in the aquatic environment and their fate and
758 removal during wastewater treatment. *Sci. Total Environ.* 473-474. 619-641. DOI:
759 <https://doi.org/10.1016/j.scitotenv.2013.12.065>

760 Matamoros, V., Rodríguez, Y., Albaigés, J., 2016. A comparative assessment of intensive and
761 extensive wastewater treatment technologies for removing emerging contaminants in small
762 communities. *Water Res.* 88, 777-785. DOI: <https://doi.org/10.1016/j.watres.2015.10.058>

763 Matamoros, V., Rodríguez, Y., Bayona, J.M., 2017. Mitigation of emerging contaminants by full-scale
764 horizontal flow constructed wetlands fed with secondary treated wastewater. *Ecol. Eng.* 99, 222-
765 227. DOI: <https://doi.org/10.1016/j.ecoleng.2016.11.054>

766 Meyer, D., Chazarenc, F., Claveau-Mallet, D., Dittmer, U., Forquet, N., Molle, P., Morvannou, A.,
767 Pálffy, T., Petitjean, A., Rizzo, A., Campà, R.S., Scholz, M., Soric, A., Langergraber, G., 2015.
768 Modelling constructed wetlands: Scopes and aims-A comparative review. *Ecol. Eng.* 80, 205-
769 213. DOI: <https://doi.org/10.1016/j.ecoleng.2014.10.031>

770 Nivala, J., Kahl, S., Boog, J., Afferden, M., Reemtsma, T., Müller, R.A., 2019. Dynamics of emerging
771 organic contaminant removal in conventional and intensified subsurface flow treatment
772 wetlands. *Sci. Total Environ.* 649, 1144-1156. DOI:
773 <https://doi.org/10.1016/j.scitotenv.2018.08.339>

774 Park, N., Vanderford, B.J., Snyder, S.A., Sarp, S., Kim, S.D., Cho, J., 2009. Effective controls of
775 micropollutants in wastewater effluent using constructed wetlands under anoxic condition. *Ecol.*
776 *Eng.* 35, 418-423. DOI: <https://doi.org/10.1016/j.ecoleng.2008.10.004>

777 Reyes-Contreras, C., Hijosa-Valsero, M., Sidrach-Cardona, R., Bayona, J.M., Bécares, E., 2012.
778 Temporal evolution in PPCP removal from urban wastewater by constructed wetlands of
779 different configuration: a medium-term study. *Chemosphere* 88, 161-167. DOI:
780 <https://doi.org/10.1016/j.chemosphere.2012.02.064>

781 Rühmland, S., Wick, A., Ternes, T.A., Barjenbruch, M., 2015. Fate of pharmaceuticals in a
782 subsurface flow constructed wetland and two ponds. *Ecol. Eng.* 80, 125-139. DOI:
783 <https://doi.org/10.1016/j.ecoleng.2015.01.036>

784 Töre, G.Y., Meriç, S., Lofrano, G., Feo, G.D., 2012. Removal of trace pollutants from wastewater in
785 constructed wetlands. Lofrano, G., (Editor), *Emerging compounds removal from wastewater,*
786 *natural and solar based Treatment.* Springer Dordrecht Heidelberg New York London. pp (39-
787 58). DOI: https://doi.org/10.1007/978-94-007-3916-1_3

788 Tran, N.H., Reinhard, M., Gin., K.Y.-H., 2018. Occurrence and fate of emerging contaminants in
789 municipal wastewater treatment plants from different geographical regions-a review. *Water Res.*
790 133, 182-207. DOI: <https://doi.org/10.1016/j.watres.2017.12.029>

791 Verlicchi, P., Galletti, A., Petrovic, M., Barceló, D., Al Aukidy, M., Zambello, E., 2013. Removal of
792 selected pharmaceuticals from domestic wastewater in an activated sludge system followed by a

793 horizontal subsurface flow bed-analysis of their respective contributions. *Sci. Total Environ.*
794 454-455, 411-425. DOI: <https://doi.org/10.1016/j.scitotenv.2013.03.044>

795 Verlicchi, P., Zambello, E., Aukidy, M.A., 2015. Removal of Personal Care Products in Constructed
796 Wetlands. *In Personal Care Products in the Aquatic Environment*; Díaz-Cruz, M.S., Barceló,
797 D., Eds.; The Handbook of Environmental Chemistry; Springer: Cham, Switzerland, 2015;
798 Volume 36, pp. 319-354. DOI: https://doi.org/10.1007/698_2014_282

799 Vo, H.-N.-P., Bui, X.-T., Nguyen, T.-M.-H., Koottatep, T., Bandyopadhyay, A., 2018. Insights of the
800 removal mechanisms of pharmaceutical and personal care products in constructed wetlands.
801 *Curr. Pollut. Rep.* 4 (2), 93-103. DOI: <https://doi.org/10.1007/s40726-018-0086-8>

802 Vymazal, J., Březinová, T., Koželuh, M., 2015. Occurrence and removal of estrogens, progesterone
803 and testosterone in three constructed wetlands treating municipal sewage in the Czech Republic.
804 *Sci. Total Environ.* 536, 625-631. DOI: <https://doi.org/10.1016/j.scitotenv.2015.07.077>

805 Vymazal, J., Březinová, T.D., Koželuh, M., Kule, L., 2017. Occurrence and removal of
806 pharmaceuticals in four full-scale constructed wetlands in the Czech Republic – the first year of
807 monitoring. *Ecol. Eng.* 98, 354-364. DOI: <https://doi.org/10.1016/j.ecoleng.2016.08.010>

808 Vystavna, Y., Frkova, Z., Marchand, L., Vergeles, Y., Stolberg, F., 2017. Removal efficiency of
809 pharmaceuticals in a full scale constructed wetland in East Ukraine. *Ecol. Eng.* 108, 50-58. DOI:
810 <https://doi.org/10.1016/j.ecoleng.2017.08.009>

811 Wang, Y., Yin, T., Kelly, B.C., Gin, K.Y.-H., 2019. Bioaccumulation behaviour of pharmaceuticals
812 and personal care products in a constructed wetland. *Chemosphere* 222, 275-285. DOI:
813 <https://doi.org/10.1016/j.chemosphere.2019.01.116>

814 Yi, X., Tran, N.H., Yin, T., He, Y., Gin, K.Y.-H., 2017. Removal of selected PPCPs, EDCs, and
815 antibiotic resistance genes in landfill leachate by a full-scale constructed wetlands system. *Water*
816 *Res.* 121, 46-60. DOI: <https://doi.org/10.1016/j.watres.2017.05.008>

817 Yin, T., Tran, N.H., Huiting, C., He, Y., Gin, K.Y.-H., 2019. Biotransformation of polyfluoroalkyl
818 substances by microbial consortia from constructed wetlands under aerobic and anoxic
819 conditions. *Chemosphere* 233, 101-109. DOI:
820 <https://doi.org/10.1016/j.chemosphere.2019.05.227>

821 Yuan, C., Huang, T., Zhao, X., Zhao, Y., 2020. Numerical Models of Subsurface Flow Constructed
822 Wetlands: Review and Future Development. *Sustainability* 12, 3498, 1-16. DOI:
823 <https://doi.org/10.3390/su12083498>

824 Zhang, D., Gersberg, R.M., Ng, W.J., Tan, S.K., 2014. Removal of pharmaceuticals and personal care
825 products in aquatic plant-based systems: a review. *Environ. Pollut.* 184, 620-639. DOI:
826 <https://doi.org/10.1016/j.envpol.2013.09.009>

827 Zhang, D.Q., Gersberg, R.M., Hua, T., Zhu, J., Tuan, N.A., Tan, S.K., 2012a. Pharmaceutical removal
828 in tropical subsurface flow constructed wetlands at varying hydraulic loading rates.
829 *Chemosphere* 87, 273-277. DOI: <https://doi.org/10.1016/j.chemosphere.2011.12.067>

830 Zhang, D.Q., Gersberg, R.M., Zhu, J., Hua, T., Jinadasa, K.B.S.N., Tan, S.K., 2012b. Batch versus
831 continuous feeding strategies for pharmaceutical removal by subsurface flow constructed
832 wetland. *Environ. Pollut.* 167, 124-131. DOI: <https://doi.org/10.1016/j.envpol.2012.04.004>

833 Zhang, X., Jing, R., Feng, X., Dai, Y., Tao, R., Vymazal, J., Cai, N., Yang, Y., 2018. Removal of
834 acidic pharmaceuticals by small-scale constructed wetlands using different design
835 configurations. *Sci. Total Environ.* 639, 640-647. DOI:
836 <https://doi.org/10.1016/j.scitotenv.2018.05.198>

Graphical abstract

Prediction of the removal efficiency of emerging organic contaminants in constructed wetlands based on their physicochemical properties

