

ELECTRONIC SUPPLEMENTARY INFORMATION

Doped sol-gel based microstructured layers to improve the light emission of luminescent coatings

Léa Marichez^{1,2}, Geneviève Chadeyron^{2*}, Daniel Zambon^{2*}, François Réveret², Audrey Potdevin², Damien Boyer², Valentin Gate³, Isabelle Verrier¹, Emilie Gamet¹, Yves Jourlin¹

¹ Laboratoire Hubert Curien UMR CNRS 5516, Université de Lyon, 18 Rue Professeur Benoît Lauras, 42000 Saint-Étienne, France

² Université Clermont Auvergne, CNRS, Clermont Auvergne INP, ICCF, F-63000 Clermont–Ferrand, France.

³ SILSEF, 382 Rue Louis Roustin, 74160 Archamps, France.




Fig. S1: Photographs of the RB solutions in ethanol (S₀₋₄): a) in daylight; b) under UV light ($\lambda_{\text{exc}} = 365 \text{ nm}$).





Fig. S2: Variation in PL QY_{abs} as a function of excitation wavelength for the solution: a) S₀; b) S₁; c) S₃; d) S₄.



a)

b)



a)

b)




Fig. S4: a) Variation in a) internal photoluminescence quantum yield $PL\text{ }QY_{int}$ and b) absorbance as a function of RB concentration in TEOS/MTEOS sols for $\lambda_{exc} = 275$, 365 and 450 nm.




Fig. S5: Emission spectra for the different solutions of RB in ethanol (S_{0-4}) ($\lambda_{\text{exc}} = 365$ nm).

a)




Fig. S6: Gaussian-type deconvolution for S_{0T} ($\lambda_{\text{exc}} = 365$ nm)

	Contribution	$E_{\max} (\text{cm}^{-1})/\lambda_{\max}$ (nm)	Area (a.u.)	FWHM (cm^{-1})
S_{0T}	1	17236 cm^{-1} (580 nm)	7763	639 cm^{-1}
	2	15875 cm^{-1} (629 nm)	540394	1139 cm^{-1}
	3	15018 cm^{-1} (665 nm)	244773	2069 cm^{-1}

Tab. S1: Deconvolution of emission spectra S_{0T} ($\lambda_{\text{exc}} = 365 \text{ nm}$) (FWHM: Full Width at Half Maximum).