



HAL
open science

Detailed study of NH_2^* chemiluminescence in ammonia combustion

Alka Karan, Maryam Khan-Ghauri, Claire M. Grégoire, Olivier Mathieu, Eric L. Petersen, Guillaume Dayma, Christian Chauveau, Fabien Halter

► **To cite this version:**

Alka Karan, Maryam Khan-Ghauri, Claire M. Grégoire, Olivier Mathieu, Eric L. Petersen, et al.. Detailed study of NH_2^* chemiluminescence in ammonia combustion. 2nd Symposium on Ammonia Energy, Université d'Orléans, Jul 2023, Orléans, France. hal-04163453

HAL Id: hal-04163453

<https://cnrs.hal.science/hal-04163453v1>

Submitted on 27 Aug 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NoDerivatives 4.0 International License

2nd Symposium on Ammonia Energy

Detailed study of NH₂* chemiluminescence in ammonia combustion

Alka Karan^{a*}, Maryam Khan-Ghauri^b, Claire M. Grégoire^b, Olivier Mathieu^b, Eric L. Petersen^b, Guillaume Dayma^a, Christian Chauveau^a, Fabien Halter^a

^aICARE- CNRS, Université d'Orléans, 1C Avenue de la Recherche Scientifique, Orléans, France

^bJ. Mike Walker '66 Department of Mechanical Engineering, Texas A&M University, College Station, TX, USA

* Corresponding author.
e-mail address: alka.karan@cnr-orleans.fr

Introduction

Ammonia combustion is of great interest as it is a zero-carbon fuel, easy to store and transport, and has a high-octane rating which is desirable in spark-ignition engines; making it an attractive fuel. Burning ammonia also comes with some disadvantages like narrow flammability limit, difficulty to ignite, and emission of NO_x in case of partial combustion. To overcome these difficulties, the flame properties must be studied. The formation of excited molecules as a result of collisions or due to chemical reactions and the subsequent emission of light as these excited molecules return to the ground state is called chemiluminescence. Chemiluminescence is a cheap and non-intrusive diagnostic tool that is often used to obtain various information on flame stabilisation, prediction of NO_x emissions [1,2], to assess the equivalence ratio [3,4], flame topology before the blowout [5] etc. On assessing the emission spectra of ammonia-air flames, it was seen that the band of NH₂* peaks that lied in the orange part of the visible spectrum dominated the spectra. It was these emissions that imparted the orange hue to the ammonia-air flames. From literature [6], it was seen that both NH₂* and NH* are good indicators of the position of the maximum heat release rate. Since the emission intensity of NH₂* is higher than NH*, it is good enough to focus on NH₂* as a first step. The aim of this work is to perform NH₂* chemiluminescence experiments in both a shock tube configuration and in a Bunsen burner configuration, to understand the chemical kinetics of NH₂*, and finally to propose and validate an NH₂* sub-mechanism using the obtained experimental data.

Materials and Methods

Shock tube

The experiments performed at Texas A&M University (TAMU) were conducted in a single-diaphragm, stainless-steel shock tube with a 3-m-long driver section (7.62 cm in diameter) and a 6.78-m-long driven section (16.2 cm in diameter). Helium was used as the driver gas, giving a test time of around 3 ms under the conditions investigated. Five piezoelectric pressure transducers (PCB 113B22) positioned near the end wall of the shock tube, with a well-known spacing between them, were used to measure the velocity of the incident shock wave so T₅ and P₅ could be calculated using 1-D shock relations. Initial composition was X_{NH₃} = 0.00605, X_{O₂} = 0.00395, X_{Ar} = 0.99000. To reduce the effect of NH₃ adsorption in the shock tube, a passivation technique was carried out prior to each experiment in the shock tube, following the procedure described in [7]. To estimate the composition of the initial mixture with accuracy post passivation, the H₂O time histories were measured during experiments with the use of a laser absorption diagnostic described in Mathieu et al. [8]. Experimental conditions were such that a plateau in the water formation was observed for each experiment. The water concentration at this plateau was then used to back calculate the composition of the original mixture (the amount of O₂ and Ar being unchanged) by fitting the profiles with existing base mechanisms. The equivalence ratio was consistently 0.32 for all runs with an error of ±0.01, indicating high repeatability in the method and a high level of wall adsorption for these very dilute mixtures, despite the passivation method.

Since the conditions behind the reflected shock waves are calculated using the mixture's composition and since the mixture composition and experimental conditions need to be implemented in the model to determine the equivalence ratio (and the temperature profile to vary the absorption coefficient as a function of the computed temperature), an iterative procedure was necessary until converging to the final values. NH_2^* measurements were taken using narrowband filters centred at 633 nm, as reported in Pugh et al. [1].

Bunsen burner

The chemiluminescence from ammonia flames was also studied by performing experiments on a Bunsen burner at atmospheric pressure for premixed ammonia-air mixtures with an equivalence ratio ranging between 0.9 and 1.4. Since ammonia flames are weak in nature, a co-flow of stoichiometric methane-air flame is used to stabilise the main flame. The effect of the pilot flame on the main flame has been studied by changing the power emitted by the pilot flame and it was observed that there was no direct influence of this pilot flame on the parameters measured in the main flame. The mean velocity of the fresh gases at the exit of the burner ranged from 0.18 to 0.2 m s^{-1} . The exposure time of the camera was set to 200 ms. An instantaneous shot is used for the study as it was seen that an average flame perturbation of over 200 images is small i.e. the induced error % in thickness is 13% for an exposure time of 200 ms. The conversion factor is $1.75 \times 10^{-2} \text{ mm pix}^{-1}$. The chemiluminescence set-up consists of a low-speed camera with high resolution (Back-illuminated sCMOS Kuro with a frame size of $2048 \times 2048 \text{ pix}^2$). A visible range objective lens is used for NH_2^* as it is found in the visible range of the emission spectra. A filter of interest is mounted upon the lens to record the emissions. For NH_2^* , a filter which is centred at 632 nm with a bandwidth of 10 nm and a diameter of 50 mm is used.

Results and Discussions

Seven different temperatures varying between 2420 K and 1899 K were studied in the TAMU shock tube. The relative NH_2^* intensity decreases with the temperature. It was observed that there are two different behaviours exhibited by the cases of high temperature and low temperature. The high temperatures are associated with steeper slopes and sharper peaks, and the lower temperatures have slopes with lower gradients and blunt peaks. For the flames, it was seen that the width of the species increased as the equivalence ratio increased. The experimental data was fitted with Gaussian curves. The peak increased up to an equivalence ratio of 1.2-1.3 and then begins to decrease.

To develop a sub-mechanism for NH_2^* , a base mechanism is required. A literature survey on the existing kinetic schemes for ammonia combustion was done and the KAUST (2021) [9] model was chosen as it predicted the evolution of species within the error bars of the experimental data obtained in a JSR, ignition delay times in a shock tube, and laminar flame speeds and provides acceptable predictions for the two sets of data presented herein. This kinetic scheme was tested and modified to fit the decomposition results of Alturaifi et al. [10] and Davidson et al. [11]. For the collision partners, the rate constants were determined by using the collision theory. Thermodynamic properties, normalised by the gas constant, are found through three polynomial fits (see Kopp et al. [12]) using seven coefficients defined for two temperature ranges, 300 K-1000 K and 1000 K-5000 K. For the flames, simulations were done for an equivalence ratio ranging between 0.9 and 1.4 and, unlike the case of the shock tube, it was seen that using the only collisional reactions was not sufficient to reproduce the experimental NH_2^* profiles' behaviour and so other chemical reactions are required.

Conclusions

From the seven different temperatures that were tested in the shock tube, experimental profiles were obtained and it was seen that higher emission intensities were associated with higher temperatures whereas from the Bunsen burner configuration, experiments were performed for equivalence ratio ranging between 0.9 and 1.4 at atmospheric conditions. It was seen that the thicker flames (i.e. higher concentrations of NH_2^*) were associated with richer flames. To model the species, collision reactions were written with rate constants determined by using the collision theory. Other reaction pathways need to be identified to predict the profiles obtained from the Bunsen burner configuration. The present model is capable of predicting the width in case of the flames. For the profiles in the shock tube configuration, the model over predicts. On further probing, it was seen that a lot of work in understanding NH_2 and NO_x chemistry is required to have a good prediction of NH_2^* .

References

- [1] D. Pugh, J. Runyon, P. Bowen, A. Giles, A. Valera-Medina, R. Marsh, B. Goktepe, S. Hewlett, An investigation of ammonia primary flame combustor concepts for emissions reduction with OH*, NH₂* and NH* chemiluminescence at elevated conditions, *Proc. Combust. Inst.* 38 (2021) 6451-6459.
- [2] X. Zhu, A. A. Khateeb, T. F. Guiberti, W. L. Roberts, NO and OH* emission characteristics of very-lean to stoichiometric ammonia–hydrogen–air swirl flames, *Proc. Combust. Inst.* 38 (2021) 5155-5162.
- [3] H. Soltanian, M.Z. Targhi, H. Pasharshahi, Chemiluminescence usage in finding optimum operating range of multi-hole burners, *Energy*. 180 (2019) 398–404.
- [4] T.S. Cheng, C.Y. Wu, Y.H. Li, Y.C. Chao, Chemiluminescence measurements of local equivalence ratio in a partially premixed flame, *Combust Sci Technol.* 178 (2006) 1821–41.
- [5] S. Wiseman, M. Rieth, A. Gruber, J. R. Dawson, J. H. Chen, A comparison of the blow-out behavior of turbulent premixed ammonia/hydrogen/nitrogen-air and methane–air flames, *Proc. Combust. Inst.* 38 (2021) 2869-2876.
- [6] A. Karan, G. Dayma, C. Chauveau, F. Halter, Insight into the inner structure of stretched premixed ammonia-air flames, *Proc. Combust. Inst.* (2022) S1540748922001067.
- [7] O. Mathieu, E. L. Petersen, Experimental and modeling study on the high-temperature oxidation of Ammonia and related NO_x chemistry, *Combust. Flame* 162 (2015) 554-570.
- [8] O. Mathieu, C. M. Grégoire, M. A. Turner, D. J. Mohr, S. A. Alturaifi, J. C. Thomas, E. L. Petersen, Experimental Investigation of the Combustion Properties of an Average Thermal Runaway Gas Mixture from Li-Ion Batteries, *Energy & Fuels* 36 (2022) 3247-3258.
- [9] X. Zhang, S. P. Moosakutty, R. P. Rajan, M. Younes, S. M. Sarathy, Combustion chemistry of ammonia/hydrogen mixtures: Jet-stirred reactor measurements and comprehensive kinetic modeling, *Combust. Flame* 234 (2021) 111653.
- [10] S. A. Alturaifi, O. Mathieu, E. L. Petersen, An experimental and modeling study of ammonia pyrolysis, *Combust. Flame* 235 (2022) 111694.
- [11] D.F. Davidson, K. Kohse-Höinghaus, A.Y. Chang, R.K. Hanson, A pyrolysis mechanism for ammonia, *Int J Chem Kinet.* 22(5) (1990) 513–35.
- [12] M. Kopp, M. Brower, O. Mathieu, E. Petersen, F. Güthe, CO₂* chemiluminescence study at low and elevated pressures, *Appl. Phys. B* 107 (2012) 529-538.