



HAL
open science

Flexible Leaky Wave Antennas for Wearable Radars

Giulia Sacco, Pratik Vadher, Denys Nikolayev

► **To cite this version:**

Giulia Sacco, Pratik Vadher, Denys Nikolayev. Flexible Leaky Wave Antennas for Wearable Radars. ICEAA-IEEE APWC 2023, Oct 2023, Venice, France. hal-04248734

HAL Id: hal-04248734

<https://cnrs.hal.science/hal-04248734>

Submitted on 18 Oct 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Flexible Leaky Wave Antennas for Wearable Radars

G. Sacco*, P. Vadher, and D. Nikolayev

IETR, University of Rennes, UMR CNRS 6164, F-35000 Rennes, France, e-mail: giulia.sacco@cnrs.fr; pratik-vinubhai.vadher@univ-rennes.fr; denys.nikolayev@cnrs.fr

Thanks to their wearability and easiness of use, on-body sensors are increasingly employed for several applications, including healthcare and sport [1]. One emerging application consists in the use of radars as electronic aids for the help of visually impaired people. Thanks to their ability to realize a 2-D map of the environment, radars allow to detect approaching obstacles and help the patients to navigate and understand the surrounding environment. However, these radars are typically included in bulky devices such as white canes, belts or glasses and are realized on entirely rigid substrates. To improve their wearability and portability issue, it is fundamental to replace the current generation of rigid devices with portable flexible sensors that could be easily integrated inside clothes. To allow for sensing the surrounding environment and communicating with other sensors or readers placed on or outside the body, these devices necessitate antennas. To ensure the comfort and the portability, antennas need to be realised on a flexible substrate conformal to the body surface. Previous studies have been reported on the feasibility of single-element resonating antennas [2], and phased arrays [3]. While the first solution does not provide reconfigurability of the radiation pattern, the second requires multiple channels and a complex feeding network to allow for the re-orientation of the beam. As a solution we propose a microstrip-based leaky-wave antenna (LWA), that, thanks to the easiness of fabrication, low cost and, low profile is a valid alternative for wearable applications (Fig. 1). While microstrip LWAs typically operate in the $n = -1$ spatial harmonic [4], in the present work, we discuss a new meandering microstrip design that operates at $n = -2$ resulting in a faster scanning rate (the ratio of beam scanning range and bandwidth). The K-band proposed antenna is based on a periodic meandering microstrip line ensuring a continuous beam scanning from backward-to-forward direction in the elevation plane. The electrical length of the unit cell is increased to make the antenna operate in a higher spatial order which increases the scanning rate. The final design shows a scanning range in the elevation plane from -40° to 45° in the frequency range 20.6–24.6 GHz, which corresponds to a scanning rate of $21.25^\circ \text{ GHz}^{-1}$ i.e., more than twice the one achievable with a traditional meandered microstrip antenna.




Figure 1. Geometry of the proposed unit cell.

This project has received funding from the European Union's Horizon Europe research and innovation programme under grant agreement N° 101063966 (Marie Skłodowska-Curie IN-SIGHT project) and from the French National Research Program for Environmental.

1. P. Soh, G. Vandenbosch, M. Mercuri, and D.-P. Schreurs, "Wearable wireless health monitoring: current developments, challenges, and future trends," *IEEE Microw. Mag.*, vol. 16, no. 4, p. 55–70.
2. N. Chahat, M. Zhadobov, R. Sauleau, and K. Ito, "A compact uwb antenna for on-body applications," *IEEE Trans. Antennas Propag.*, vol. 59, no. 4, p. 1123–1131.
3. D. Anagnostou, "Flexible arrays signal change in communications," *Nat. Electron.*, vol. 2, no. 5, Art. no. 5.
4. H. Jiang, K. Xu, Q. Zhang, Y. Yang, D. K. Karmokar, S. Chen, P. Zhao, G. Wang, and L. Peng, "Backward-to-forward wide-angle fast beam-scanning leaky-wave antenna with consistent gain," *IEEE Transactions on Antennas and Propagation*, vol. 69, no. 5, pp. 2987–2992, May 2021.