

Stability analysis of a class of 2 x 2 triangular hyperbolic systems

Mohand Ouidir Amirat, Vincent Andrieu, Jean Auriol, Mathieu Bajodek, C. Valentin

▶ To cite this version:

Mohand Ouidir Amirat, Vincent Andrieu, Jean Auriol, Mathieu Bajodek, C. Valentin. Stability analysis of a class of 2 x 2 triangular hyperbolic systems. 2024. hal-04531360

HAL Id: hal-04531360 https://cnrs.hal.science/hal-04531360

Preprint submitted on 5 Apr 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Stability analysis of a class of 2×2 triangular hyperbolic systems

M.O. Amirat * V. Andrieu * J. Auriol ** M. Bajodek * C. Valentin *

* Laboratoire d'Automatique, de Génie des Procédés et de Génie Pharmaceutique (LAGEPP), UMR CNRS 5007, Université Claude Bernard Lyon 1, Lyon France

** Laboratoire des signaux et systèmes (L2S), UMR CNRS 8506, CentraleSupélec - Université Paris-Saclay, Gif-sur-Yvette, France

Abstract: In this paper, the stability analysis of a class of hyperbolic systems with non-diagonalizable principal part and nonuniform coefficients is addressed. We give a stability condition and express the convergence rate that can be obtained. Two cases will be treated independently: with and without a source term. A numerical scheme is designed to illustrate the performance of the Lyapunov stability analysis.

Keywords: Linear PDE, Weakly triangular hyperbolic system, Stability analysis, Strict Lyapunov functional.

1. INTRODUCTION

In recent years, significant progress has been made in understanding the stability and control of strictly hyperbolic systems, thanks to the contributions of Bastin and Coron (2016), among others. In particular, control strategies for hyperbolic systems using backstepping with Volterra or Fredholm transformations have been proposed Krstic (2009); Bribiesca-Argomedo and Krstic (2015); Coron et al. (2013). These mathematical advances can then be applied to a wide range of applications, such as drilling processes Bresch-Pietri and Krstic (2014), navigable rivers (Bastin and Coron, 2016, Chapter 8) or wastewater treatment Valentin et al. (2023).

However, as soon as the system is weakly hyperbolic, for instance having a non-diagonalisable principal part with eigenvalues of multiplicity greater than one, only few stability results and even fewer control results are available (see however Alabau-Boussouira (2002); Métivier and Zumbrun (2005)). In this paper, we deal with the case of hyperbolic systems of dimension 2×2 when the principal part has a positive eigenvalue of geometric multiplicity equal to two, at least on a part of the spatial domain.

By leveraging Lyapunov analysis, a strict Lyapunov functional is designed which, under certain conditions, allows us to assess the global exponential stability. This Lyapunov functional relies heavily on input-to-state properties Prieur and Mazenc (2012) satisfied by our class of system. In addition, we have endeavored to get as close as possible to the optimum bounds Lamare et al. (2016) on the convergence rate and the overshoot. To achieve this, we played with different weights, in particular using polynomial rather than exponential weights in the Lyapunov functional kernels.

Section 2 introduces the system class, along with the accompanying definitions and the statement of the problem. In Section 3, two stability conditions are presented, differentiating between cases with and without a source term. Section 4 illustrates the theoretical findings through the simulation of two academic examples.

Notation: Throughout the paper, the partial derivatives in time and space are denoted ∂_t and ∂_x , while the classical derivative are $\dot{\mathcal{V}}=\frac{\mathrm{d}}{\mathrm{d}t}\mathcal{V}$ and . Moreover, $C^k_{pw}(0,1;\mathbb{R})$ denotes the space of functions defined from [0,1] to \mathbb{R} for which the k-1 first derivatives are continuous and the k-th derivative is piece-wise continuous; $L^2((0,1);\mathbb{R})$ denotes the space of square-integrable functions from (0,1) to \mathbb{R} ; $H^1((0,1);\mathbb{R})=\{f:(0,1)\to\mathbb{R}\mid f\in L^2((0,1);\mathbb{R}), f'\in L^2((0,1);\mathbb{R})\}$ and $X=L^2((0,1);\mathbb{R})\times H^1((0,1);\mathbb{R})$ equipped with the norm:

$$\begin{split} \|\cdot\|_X^2 : (f,g) &\mapsto \|f\|_{L^2((0,1),\mathbb{R})}^2 + \|g\|_{L^2((0,1);\mathbb{R})}^2 + \|g'\|_{L^2((0,1);\mathbb{R})}^2. \\ \text{Given a function } f : (0,1) &\mapsto \mathbb{R}, \text{ we denote by } \overline{f} = \\ \max\left\{0, \sup_{x \in (0,1)} f(x)\right\} \text{ and } \underline{f} = \inf_{x \in (0,1)} f(x). \end{split}$$

2. PROBLEM STATEMENT

Consider the following class of triangular 2x2 hyperbolic system

$$\begin{cases} \partial_t \phi(t,x) = \Lambda(x) \left(A(x) \partial_x \phi(t,x) + B(x) \phi(t,x) \right), & x \in (0,1), \\ \phi(t,1) = D\phi(t,0), \\ \phi(0,x) = \phi^0(x) \end{cases}$$

(1)

with $\phi(t, x) = (\phi_1(t, x), \phi_2(t, x)) \in X$ being the state of the system defined for any $t \geq 0$ and any $x \in [0, 1], \phi^0 \in X$ a given initial condition satisfying zero-order and first-order compatibility conditions Bastin and Coron (2016).

We have $\Lambda(x) = \begin{bmatrix} \lambda_1(x) & 0 \\ 0 & \lambda_2(x) \end{bmatrix}$ is such that $\lambda_{1,2}(x) > 0$, moreover we assume that $\lambda_1 \in C^0_{pw}(0,1;\mathbb{R})$ and $\lambda_2 \in C^1_{pw}(0,1;\mathbb{R})$, $A(x) = \begin{bmatrix} 1 & c(x) \\ 0 & 1 \end{bmatrix}$ where $c \in C^0_{pw}(0,1;\mathbb{R})$, the source term $B(x) = \begin{bmatrix} B_{11}(x) & B_{12}(x) \\ 0 & B_{22}(x) \end{bmatrix}$ is continuous, we assume $B_{11}, B_{12} \in C^0_{pw}(0,1;\mathbb{R})$, $B_{22} \in C^1_{pw}(0,1;\mathbb{R})$ and $D = \begin{bmatrix} D_{11} & D_{12} \\ 0 & D_{22} \end{bmatrix}$.

System (1) is worth of interest in cases where the principal part A(x) is not diagonalizable for some part of the space $x \in (0,1)$, in other words if there exists $x \in (0,1)$ such that $\lambda_1(x) = \lambda_2(x)$ and if for all $x \in (0,1)$, $c(x) \neq 0$.

Lemma 1. For any initial condition $\phi(0) = \phi^0 \in X$, the system (1) is well-posed and the (weak) solution $t \mapsto \phi(t;\phi^0)$ belongs to $C([0,+\infty);X)$ for all $t \geq 0$.

Definition 1. The origin of system (1) is said to be globally δ -exponentially stable if there exists an overshoot $\kappa \geq 1$ and a decay rate $\delta > 0$ such that for any initial condition $\phi^0 \in X$:

$$\|\phi(t;\phi^0)\|_X^2 \le \kappa e^{-\delta t} \|\phi^0\|_X^2, \ \forall t \ge 0.$$

In this paper, we aim at giving sufficient conditions that ensures exponential stablility of system (1) in the sense of Definition 1.

3. STABILITY ANALYSIS

3.1 First study case: without the source term

In this section, we express a stability condition on system (1) in the case where the source term, B, is null. This one imposes a restriction on the diagonal terms of D with respect to the function λ_2 .

Assumption 1. The function λ_2 and the matrix D satisfy the following inequality

$$\max(D_{11}^2, D_{22}^2) < 1 - \frac{\overline{\lambda_2}}{\lambda_2}.$$
 (2)

Based on this assumption, we can now give the following result which establishes exponential stability of the origin and gives an estimate on the exponential convergence rate and the overshoot.

Theorem 1. Assume B=0. Let Assumption 1 holds and let $\nu:=\frac{\overline{\lambda_2'}}{\frac{\lambda_2}{(1+\bar{\nu})}}$, $\bar{\nu}:=\frac{1-D_{22}^2}{D_{22}^2}$. Then, for any $\delta<\min\{\frac{\bar{\nu}\underline{\lambda}_1}{1+\bar{\nu}},\frac{\bar{\nu}\underline{\lambda}_2}{1+\bar{\nu}},\frac{\bar{\nu}\underline{\lambda}_2}{(1+\bar{\nu})(1+\nu)}\}$, the origin of system (1) is δ -exponentially stable with an overshoot given by

$$\kappa = \frac{\frac{1}{\lambda_1} + \frac{\alpha_{20}}{\lambda_2} + \frac{\alpha_{21}}{\lambda_2}}{\min(\frac{1}{\lambda_1}, \frac{\alpha_{20}}{\lambda_2}, \frac{\alpha_{21}}{\lambda_2})} (1 + \bar{\nu} - \frac{\varepsilon}{2}), \quad 0 < \varepsilon < \bar{\nu} - \nu,$$

and α_{20}, α_{21} given by (10).

With Assumption 1, it can be checked that ν , $\bar{\nu}$ and δ which appear in the statement of Theorem 1 are all well defined and positive.

Remark 1. Note that this result is inspired by Diagne et al. (2012); Prieur and Mazenc (2012) and extends (Bastin and Coron, 2016, Theorem 6.10) for the case of triangular hyperbolic structure. For the diagonal case, i.e. c=0 and when $\lambda_2'=0$, we recover the well-known stability condition $|D_{11}|<1$ and $|D_{22}|<1$ (i.e. D is a Schur matrix).

Remark 2. This result is establishes due to the cascade structure of system (1). With assumption 1, it can be shown that the origin of the first subsystem with state ϕ_2 is globally exponentially stable in H^1 norm for any decay rate smaller than $\bar{\nu}\underline{\lambda}_2$ whereas the origin of the second part of state ϕ_1 is input-to-state stable with respect to the H^1 norm of ϕ_2 .

Remark 3. The presence of the non diagonal term c in the system definition forces us to work with the $L^2 \times H^1$ norm (see Garetto et al. (2018)). We found that when $D_{21} \neq 0$, the term $D_{21}\partial_x\phi_2(0)\partial_x\phi_1(0)$ in the stability analysis cannot be handled. It remains unclear whether the system (1) is stable at the origin when $D_{21} \neq 0$. Our numerical observations suggest that the presence of this term significantly affects the convergence properties of the system.

Proof. The method used to prove Theorem 1 relies on the construction of a Lyapunov functional inspired by Kharitonov (2012); Krstic (2009). Consider the following functional:

$$\mathcal{V}(\phi) = \int_0^1 \phi^\top(x) P(x) \phi(x) dx + \int_0^1 \partial_x \phi^\top(x) Q(x) \partial_x \phi(x) dx,$$
(3)

with matrices P(x) and Q(x) given by

$$P(x) = \begin{bmatrix} \frac{1+\mu x}{\lambda_1(x)} & 0 \\ 0 & \alpha_{20} \frac{1+\mu x}{\lambda_2(x)} \end{bmatrix}, \quad Q(x) = \begin{bmatrix} 0 & 0 \\ 0 & \alpha_{21} \frac{1+\mu x}{\lambda_2(x)} \end{bmatrix},$$

and scalars μ , α_{20} , $\alpha_{21} > 0$.

This functional will be decomposed term by term as follows: $V(\phi) = V_1(\phi) + \alpha_{20}V_{20}(\phi) + \alpha_{21}V_{21}(\phi)$ with

$$\mathcal{V}_{1}(\phi) = \int_{0}^{1} \frac{1+\mu x}{\lambda_{1}(x)} \phi_{1}^{2}(x) dx,$$

$$\mathcal{V}_{20}(\phi) = \int_{0}^{1} \frac{1+\mu x}{\lambda_{2}(x)} \phi_{2}^{2}(x) dx,$$

$$\mathcal{V}_{21}(\phi) = \int_{0}^{1} \frac{1+\mu x}{\lambda_{2}(x)} (\partial_{x} \phi_{2})^{2}(x) dx$$

First, we assess the following inequalities :

$$\min\left(\frac{1}{\overline{\lambda_{1}}}, \frac{\alpha_{20}}{\overline{\lambda_{2}}}, \frac{\alpha_{21}}{\overline{\lambda_{2}}}\right) \|\phi\|_{X} \leq \mathcal{V}(\phi),$$

$$\mathcal{V}(\phi) \leq \left(\frac{1+\mu}{\underline{\lambda_{1}}} + \alpha_{20} \frac{1+\mu}{\underline{\lambda_{2}}} + \alpha_{21} \frac{1+\mu}{\underline{\lambda_{2}}}\right) \|\phi\|_{X},$$
(4)

Along C^1 solutions to system (1) with B=0, the time derivative of each term of this functional is calculated below.

First, we obtain

$$\dot{\mathcal{V}}_{20}(\phi) = 2 \int_0^1 (1 + \mu x) \phi_2(x) \partial_x \phi_2(x) dx,$$

$$= -\mu \int_0^1 \phi_2^2(x) dx + (1 + \mu) \phi_2^2(1) - \phi_2^2(0)$$

As $\phi_2(1) = D_{22}\phi_2(0)$, and since by Assumption 1, $|D_{22}| < 1$, we have

$$\dot{\mathcal{V}}_{20}(\phi) \le -\mu \|\phi_2\|_{L^2}^2 + (\mu - \bar{\nu})\phi_2^2(1).$$
 (5)

Second, in the same way, we obtain

$$\dot{\mathcal{V}}_{1}(\phi) = 2 \int_{0}^{1} (1 + \mu x) \phi_{1}(x) \partial_{x} \phi_{1}(x) dx$$

$$+ 2 \int_{0}^{1} c(x) (1 + \mu x) \phi_{1}(x) \partial_{x} \phi_{2}(x) dx,$$

$$= -\mu \int_{0}^{1} \phi_{1}^{2}(x) dx + (1 + \mu) \phi_{1}^{2}(1) - \phi_{1}^{2}(0)$$

$$+ 2 \int_{0}^{1} c(x) (1 + \mu x) \phi_{1}(x) \partial_{x} \phi_{2}(x) dx.$$

For any $a, b \in L^2((0,1); \mathbb{R})$ and $\gamma > 0$, Young's inequality ensures

$$2\int_0^1 a(x)b(x)dx \le \gamma \int_0^1 a^2(x)dx + \frac{1}{\gamma} \int_0^1 b^2(x)dx.$$

Taking $a(x) = |\phi_1(x)|$ and $b(x) = |\partial_x \phi_2(x)|$, the crossed term can be bounded as follows

$$\begin{split} &2\int_0^1 c(x)(1+\mu x)\phi_1(x)\partial_x\phi_2(x)\mathrm{d}x\\ &\leq (1+\mu)\overline{c}\left(\gamma\int_0^1\phi_1^2(x)\mathrm{d}x + \frac{1}{\gamma}\!\!\int_0^1\!\!(\partial_x\phi_2)^2(x)\mathrm{d}x\right)\\ &\leq (1+\mu)\overline{c}\left(\gamma\|\phi_1\|_{L^2}^2 + \frac{1}{\gamma}\|\partial_x\phi_2\|_{L^2}^2\right) \end{split}$$

with $\overline{c} = \max_{x \in (0,1)} |c(x)|$. Hence, the time derivative of \mathcal{V}_1 is bounded by

$$\dot{\mathcal{V}}_{1}(\phi) \leq (-\mu + (1+\mu)\overline{c}\gamma) \|\phi_{1}\|_{L^{2}}^{2} + \frac{(1+\mu)\overline{c}}{\gamma} \|\partial_{x}\phi_{2}\|_{L^{2}}^{2} + (1+\mu)(D_{11}\phi_{1}(0) + D_{12}\phi_{2}(0))^{2} - \phi_{1}^{2}(0)$$

Moreover, Young's inequality ensures

$$(1 + \mu)(D_{11}\phi_1(0) + D_{12}\phi_2(0))^2 - \phi_1^2(0)$$

$$\leq (D_{11}^2 - 1)\phi_1^2(0) + D_{12}^2\phi_2^2(0) + D_{11}D_{12}(a\phi_1^2(0) + \frac{1}{a}\phi_2^2(0)),$$

$$\leq (D_{11}^2 - 1 + a|D_{11}D_{12}|)\phi_1^2(0) + (D_{12}^2 + \frac{|D_{11}D_{12}|}{a})\phi_2^2(0).$$

Since by Assumption 1, $|D_{11}| < 1$, picking μ sufficiently small it yields that

$$a := \frac{1 - (1 + \mu)D_{11}^2}{(1 + \mu)|D_{11}D_{12}|} > 0.$$
 (6)

Consequently, it implies

$$\dot{\mathcal{V}}_1(\phi) \le (-\mu + \beta \gamma) \|\phi_1\|_{L^2}^2 + \alpha \phi_2^2(1) + \frac{\beta}{\gamma} \|\partial_x \phi_2\|_{L^2}^2, \quad (7)$$

with

$$\alpha = \frac{(1+\mu)}{D_{22}^2} \left(D_{12}^2 + \frac{|D_{11}D_{12}|}{a} \right) = \left(\frac{1+\mu}{1 - (1+\mu)D_{11}^2} \right) \frac{D_{12}^2}{D_{22}^2},$$

$$\beta = (1+\mu)\bar{c}.$$

Third, similarly, the time derivative of the last part of the Lyapunov candidate functional yields

$$\begin{split} \dot{\mathcal{V}}_{21}(\phi) &= 2 \int_{0}^{1} (1 + \mu x) \partial_{x} \phi_{2}(x) \frac{\partial_{xt} \phi_{2}(x)}{\lambda_{2}(x)} \mathrm{d}x, \\ &= 2 \int_{0}^{1} (1 + \mu x) \partial_{x} \phi_{2}(x) \partial_{xx} \phi_{2}(x) \mathrm{d}x \\ &+ 2 \int_{0}^{1} (1 + \mu x) \frac{\lambda_{2}'(x)}{\lambda_{2}(x)} (\partial_{x} \phi_{2})^{2}(x) \mathrm{d}x, \\ &= -\mu \int_{0}^{1} (\partial_{x} \phi_{2})^{2}(x) \mathrm{d}x + (1 + \mu) \partial_{x} \phi_{2}^{2}(1) - \partial_{x} \phi_{2}^{2}(0) \\ &+ 2 \int_{0}^{1} (1 + \mu x) \frac{\lambda_{2}'(x)}{\lambda_{2}(x)} (\partial_{x} \phi_{2})^{2}(x) \mathrm{d}x. \end{split}$$

As $\partial_x \phi_2(1) = D_{22} \partial_x \phi_2(0)$ from the compatibility condition, we have

$$\dot{\mathcal{V}}_{21}(\phi) \le (-\mu + 2(1+\mu)\frac{\overline{\lambda_2}}{\lambda_2}) \|\partial_x \phi_2\|_{L^2}^2 + (\mu - \bar{\nu})\partial_x \phi_2^2(1). \tag{8}$$

Considering $\nu = (1 - \frac{\overline{\lambda_2'}}{\underline{\lambda_2}})^{-1} \frac{\overline{\lambda_2'}}{\underline{\lambda_2}}$ is equivalent to $\frac{\overline{\lambda_2'}}{\underline{\lambda_2}} = \frac{\nu}{1+\nu}$ which means that $(-\mu + 2(1+\mu)\frac{\overline{\lambda_2'}}{\underline{\lambda_2}}) = \frac{\nu-\mu}{1+\nu}$. Thus, from (5), (7) and (8), we end up with

$$\dot{\mathcal{V}}(\phi) \leq (-\mu + \beta \gamma) \|\phi_{1}\|_{L^{2}}^{2} - \alpha_{20}\mu \|\phi_{2}\|_{L^{2}}^{2}
+ \left(\frac{\beta}{\gamma} + \alpha_{21} \frac{\nu(2+\mu)-\mu}{1+\nu}\right) \|\partial_{x}\phi_{2}\|_{L^{2}}^{2}
+ (\alpha_{20}(\mu - \bar{\nu}) + \alpha) \phi_{2}^{2}(1)
+ \alpha_{21}(\mu - \bar{\nu})\partial_{x}\phi_{2}^{2}(1).$$
(9)

To make the last three terms negative, we select the positive scalars μ , α_{20} , α_{21} , γ as follows

$$\mu = \bar{\nu} - \frac{\varepsilon}{2}, \qquad \gamma = \frac{\mu - \bar{\nu} + \varepsilon}{\beta} = \frac{\varepsilon}{2\beta}$$

$$\alpha_{20} = \frac{1}{(\bar{\nu} - \mu)} \alpha = \frac{2\alpha}{\varepsilon},$$

$$\alpha_{21} = \frac{1 + \nu}{\mu - \nu(2 + \mu) - (\bar{\nu} - \nu - \varepsilon)} \frac{\beta}{\gamma} = \frac{4(1 + \nu)\beta^2}{\varepsilon^2}.$$
(10)

and sufficiently small scalar ε verifying $\varepsilon < \bar{\nu} - \nu$. With Assumption 1, $\frac{\overline{\lambda_2}}{\overline{\lambda_2}} < 1 - D_{22}^2$, hence, we clearly check that $\nu < \mu < \bar{\nu}$ holds. Then, as:

$$\begin{aligned} \|\phi_1\|_{L^2}^2 &\geq \frac{\lambda_1}{1+\mu} \mathcal{V}_1(\phi) \geq \frac{\lambda_1}{1+\bar{\nu}} \mathcal{V}_1(\phi), \\ \|\phi_2\|_{L^2}^2 &\geq \frac{\lambda_2}{1+\mu} \mathcal{V}_{20}(\phi) \geq \frac{\lambda_2}{1+\bar{\nu}} \mathcal{V}_{20}(\phi), \\ \|\partial_x \phi_2\|_{L^2}^2 &\geq \frac{\lambda_2}{1+\mu} \mathcal{V}_{21}(\phi) \geq \frac{\lambda_2}{1+\bar{\nu}} \mathcal{V}_{21}(\phi), \end{aligned}$$

the time derivative of the Lyapunov candidate functional along \mathbb{C}^1 solutions of system (1) satisfy

$$\dot{\mathcal{V}}(\phi) \leq -(\overline{\nu} - \varepsilon) \frac{\underline{\lambda}_1}{1+\overline{\nu}} \mathcal{V}_1(\phi) - \alpha_{20}(\overline{\nu} - \frac{\varepsilon}{2}) \frac{\underline{\lambda}_2}{1+\overline{\nu}} \mathcal{V}_{20}(\phi) - \alpha_{21} \frac{\overline{\nu} - \nu - \varepsilon}{1+\nu} \frac{\underline{\lambda}_2}{1+\overline{\nu}} \mathcal{V}_{21}(\phi)$$

meaning for sufficiently small scalar ε that

$$\dot{\mathcal{V}}(\phi) \le -\delta \mathcal{V}(\phi),\tag{11}$$

for any $\delta < \min\{\frac{\bar{\nu}\underline{\lambda}_1}{1+\bar{\nu}}, \frac{\bar{\nu}\underline{\lambda}_2}{1+\bar{\nu}}, \frac{(\bar{\nu}-\nu)\underline{\lambda}_2}{(1+\bar{\nu})(1+\nu)}\}$. With Grönwall inequality the above equation (11), and by standard density arguments yields

$$\mathcal{V}(\phi(t;\phi_0)) \le e^{-\delta t} \mathcal{V}(\phi^0), \ \forall \phi^0 \in X.$$

To conclude, using the equivalence of norm (4),

$$\left\|\phi(t;\phi^0)\right\|_X^2 \leq \kappa e^{-\delta t} \left\|\phi^0\right\|_X$$

holds with κ and δ given explicitely independtly from the initial condition, which allows us to close the proof.

In this section, we consider the case in which the source term B is non null. The new assumption that we consider is given as follows.

Assumption 2. Assume that the functions λ_2 , B and the matrix D satisfy

$$1 - \max \left\{ 2\overline{B_{11}}, \frac{\overline{\lambda_2'}}{\underline{\lambda_2}} + 2\overline{B_{22}} \right\} > \max(D_{11}^2, D_{22}^2). \tag{12}$$

With this assumption, the following theorem can be obtained.

Theorem 2. Let Assumption 2 holds and let

$$\nu_{1} := 2\overline{B_{11}}(1 - 2\overline{B_{11}})^{-1},
\nu_{2} := \frac{\overline{\lambda_{2}} + 2\lambda_{2}\overline{B_{22}}}{\underline{\lambda_{2}} - \overline{\lambda_{2}} - 2\underline{\lambda_{2}}\overline{B_{22}}},
\bar{\nu} := \frac{1 - D_{22}^{2}}{D_{22}^{2}}.$$
(13)

Then, for any $\delta < \min\{\delta_1, \delta_2\}$ where $\delta_1 = \frac{\underline{\lambda}_1(\bar{\nu}-\nu_1)}{(1+\nu_1)(1+\bar{\nu})}$ and $\delta_2 = \frac{\underline{\lambda}_2(\bar{\nu}-\nu_2)}{(1+\nu_2)(1+\bar{\nu})}$, system (1) is δ -exponentially stable with an overshoot given by

$$\kappa = \frac{\frac{1}{\lambda_1} + \frac{\alpha_{20}}{\lambda_2} + \frac{\alpha_{21}}{\lambda_2}}{\min(\frac{1}{\lambda_1}, \frac{\alpha_{20}}{\lambda_2}, \frac{\alpha_{21}}{\lambda_2})} (1 + \bar{\nu} - \frac{\varepsilon}{2}), \quad 0 < \varepsilon < \bar{\nu} - \max\{\nu_1, \nu_2\},$$

and α_{20}, α_{21} given by (18).

In this second theorem, the stability is obtained under several conditions. As previously, the ratio between diagonal velocities and its derivatives must be small. In addition, the diagonal coefficients of the source term must be upper-bounded (a fortiori when B_{11} and B_{22} are negative Assumption 2 reduces to Assumption 1).

Remark 4. This result extends (Bastin and Coron, 2016, Theorem 6.10) from strictly hyperbolic to a class of weakly hyperbolic systems. For the strict case, i.e. c=0, we fall back to the well-known stability condition $B_{11}, B_{22} < 0$ (B a Hurwitz matrix).

Remark 5. Note that the case $c \neq 0$ and $\lambda_1 = \lambda_2$ imposes the constraint $B_{21} = 0$ in our Lyapunov analysis. Indeed, when $B_{21} \neq 0$, a term in $\int_0^1 B_{21}(x) \partial_x \phi_2(x) \partial_x \phi_1(x) dx$ appears and cannot be compensated in the absence of negativity on the H^1 norm of the state ϕ_1 . A deeper analysis should be carried out to handle full matrices B.

Proof. Note that with Assumption 2, ν_1 , ν_2 are positive and all the constant involved in the statement of the theorem are well defined. Consider the functional $\mathcal{V} = \mathcal{V}_1 + \alpha_{20}\mathcal{V}_{20} + \alpha_{21}\mathcal{V}_{21}$ expressed in (3) with scalars μ , α_{20} , $\alpha_{21} > 0$ to be fixed later. The equivalence of norm (4) is still verified. Let us now repeat the time derivation of each of the three terms along the C^1 trajectories of system (1) and let us focus on the additional terms that will be denoted $\mathcal{W}_1, \mathcal{W}_{20}, \mathcal{W}_{21}$ coming from the source term.

First, we obtain

$$W_{20}(\phi) = 2 \int_0^1 (1 + \mu x) B_{22}(x) \phi_2^2(x) dx,$$

leading to

$$W_{20}(\phi) \le 2(1+\mu)\overline{B_{22}} \|\phi_2\|_{L^2}^2. \tag{14}$$

Second, we obtain

$$W_1(\phi) = 2 \int_0^1 (1+\mu x) \left(B_{11}(x)\phi_1^2(x) + B_{12}(x)\phi_1(x)\phi_2(x) \right) dx.$$

Applying Young's inequality, for any $\gamma_1 > 0$, it leads to

$$W_1(\phi) \le (1+\mu) \left((2\overline{B_{11}} + \gamma_1 |\overline{B_{12}}|) \|\phi_1\|_{L^2}^2 + \frac{\overline{|B_{12}|}}{\gamma_1} \|\phi_2\|_{L^2}^2 \right), \tag{15}$$

Third, we obtain

$$W_{21} = 2 \int_0^1 (1 + \mu x) B_{22}(x) \partial_x \phi_2^2(x) dx,$$

+2 \int_0^1 (1 + \mu x) \frac{(\lambda_2 B_{22})'(x)}{\lambda_2(x)} \partial_x \phi_2(x) \phi_2(x) dx.

Applying Young's inequality, for any $\gamma_2 > 0$, it leads to

$$\mathcal{W}_{21}(\phi) \leq (1+\mu) \left(2\overline{B}_{22} + \gamma_2 \frac{\overline{(\lambda_2 B_{22})'}}{\frac{\lambda_2}{2}} \right) \|\partial_x \phi_2\|_{L^2}^2 + (1+\mu) \frac{1}{\gamma_2} \frac{\overline{(\lambda_2 B_{22})'}}{\frac{\lambda_2}{2}} \|\phi_2\|_{L^2}^2$$
(16)

To sum up inequations (9), (14), (15) and (16), we have: $\dot{\mathcal{V}}(\phi) \leq \left[-\mu + 2(1+\mu)\overline{B_{11}} + \gamma\beta + \gamma_1\beta_1 \right] \|\phi_1\|_{L^2}^2 \\ + \left[\alpha_{20} \left(-\mu + 2(1+\mu)\overline{B_{22}} + \frac{\alpha_{21}}{\alpha_{20}} \frac{\beta_2}{\gamma_2} \right) + \frac{\beta_1}{\gamma_1} \right] \|\phi_2\|_{L^2}^2 \\ + \left[\alpha_{21} \left(-\mu + (1+\mu)(\frac{\overline{\lambda_2'}}{\underline{\lambda_2}} + 2\overline{B}_{22}) + \gamma_2\beta_2 \right) + \frac{\beta}{\gamma} \right] \|\partial_x\phi_2\|_{L^2}^2 \\ + \left(\alpha_{20}(\mu - \bar{\nu}) + \alpha \right) \phi_2^2(1) + \alpha_{21}(\mu - \bar{\nu}) \partial_x\phi_2^2(1).$ with

$$\beta_1 = (1+\mu)\overline{|B_{12}|}, \quad \beta_2 = (1+\mu)\frac{(\overline{\lambda_2 B_{22}})'}{\lambda_2}.$$

From expression (13) we have

$$2\overline{B_{11}} = \tfrac{\nu_1}{1+\nu_1}, \quad \tfrac{\overline{\lambda_2'}}{\underline{\lambda_2}} + 2\overline{B_{22}} = \tfrac{\nu_2}{1+\nu_2}.$$

Thus

$$\begin{split} \dot{\mathcal{V}}(\phi) &\leq \left[\frac{\nu_{1} - \mu}{1 + \nu_{1}} + \gamma \beta + \gamma_{1} \beta_{1} \right] \|\phi_{1}\|_{L^{2}}^{2} \\ &+ \left[\alpha_{20} \left(\frac{\nu_{2} - \mu}{1 + \nu_{2}} + \frac{\alpha_{21}}{\alpha_{20}} \frac{\beta_{2}}{\gamma_{2}} \right) + \frac{\beta_{1}}{\gamma_{1}} \right] \|\phi_{2}\|_{L^{2}}^{2} \\ &+ \left[\alpha_{21} \left(\frac{\nu_{2} - \mu}{1 + \nu_{2}} + \gamma_{2} \beta_{2} \right) + \frac{\beta}{\gamma} \right] \|\partial_{x} \phi_{2}\|_{L^{2}}^{2} \\ &+ \left(\alpha_{20} (\mu - \bar{\nu}) + \alpha \right) \phi_{2}^{2}(1) + \alpha_{21} (\mu - \bar{\nu}) \partial_{x} \phi_{2}^{2}(1). \end{split}$$

Similarly to (10), we begin with setting $\mu, \gamma, \gamma_1, \gamma_2$ as follows

$$\mu = \bar{\nu} - \frac{\varepsilon}{2}, \qquad \gamma = \frac{\varepsilon}{4(1+\nu_1)\beta},$$

$$\gamma_1 = \frac{\varepsilon}{4(1+\nu_1)\beta_1}, \quad \gamma_2 = \frac{\varepsilon}{4(1+\nu_2)\beta_2}.$$
(17)

to obtain

$$\begin{split} \dot{\mathcal{V}}(\phi) &\leq \frac{\nu_{1} - \bar{\nu} + \varepsilon}{1 + \nu_{1}} \|\phi_{1}\|_{L^{2}}^{2} \\ &+ \left[\alpha_{20} \frac{\nu_{2} - \bar{\nu} + \frac{\varepsilon}{2}}{1 + \nu_{2}} + \alpha_{21} \frac{4(1 + \nu_{2})\beta_{2}^{2}}{\varepsilon} + \frac{4(1 + \nu_{1})\beta_{1}^{2}}{\varepsilon} \right] \|\phi_{2}\|_{L^{2}}^{2} \\ &+ \left[\alpha_{21} \frac{\nu_{2} - \bar{\nu} + \frac{3\varepsilon}{4}}{1 + \nu_{2}} + \frac{4(1 + \nu_{1})\beta^{2}}{\varepsilon} \right] \|\partial_{x}\phi_{2}\|_{L^{2}}^{2} \\ &+ \left(-\alpha_{20} \frac{\varepsilon}{2} + \alpha \right) \phi_{2}^{2}(1) - \alpha_{21} \frac{\varepsilon}{2} \partial_{x} \phi_{2}^{2}(1). \end{split}$$

Finally, we set α_{20}, α_{21} as

$$\alpha_{20} = \max \left\{ \frac{2\alpha}{\varepsilon}, \alpha_{21} \frac{16(1+\nu_2)^2 \beta_2^2}{\varepsilon^2}, \frac{16(1+\nu_2)(1+\nu_1)\beta_1^2}{\varepsilon^2} \right\},$$

$$\alpha_{21} = \frac{16(1+\nu_1)(1+\nu_2)\beta^2}{\varepsilon^2}.$$
(18)

to achieve

 $\dot{\mathcal{V}}(\phi) \leq$

$$\frac{\nu_1 - \bar{\nu} + \varepsilon}{1 + \nu_1} \|\phi_1\|_{L^2}^2 + \alpha_{20} \frac{\nu_2 - \bar{\nu} + \varepsilon}{1 + \nu_2} \|\phi_2\|_{L^2}^2 + \alpha_{21} \frac{\nu_2 - \bar{\nu} + \varepsilon}{1 + \nu_2} \|\partial_x \phi_2\|_{L^2}^2.$$

Then, selecting ε small enough, the time derivative of the Lyapunov candidate functional along the trajectories of system (1) satisfies $\mathcal{V}(\phi) \leq -\delta \mathcal{V}(\phi)$ for all $\delta < \min(\delta_1, \delta_2)$ and the equivalence of norm (4) ends the proof.

4. NUMERICAL RESULTS

In this numerical results section, we make use of several challenging test cases to illustrate the performance of the Lyapunov stability analysis approach proposed in the previous section for system (1).

System (1) represents a coupling of two transport equations with negative velocities. In order to design a numerical discretization of the PDEs system, we consider an upwind type explicit finite difference scheme that takes into account the directions of waves propagation (see LeVeque (2002)).

We denote the space-time domain $\mathcal{D} = [0,1] \times [0,T]$, T being the final time for system (1) dynamics. A discretization of this continuous domain is made; given $p \in \mathbb{N}^*$ sufficiently large, we introduce the space mesh-size as $\Delta x = \frac{1}{p+1}$. Such procedure generates a sequence of grid points $(x_i, t^n) = (i\Delta x, n\Delta t), i \in [0..p+1], n \in \mathbb{N}^*$. The time-stepping increment Δt will be specified later on.

Approximations of the states of system (1) will be made on the grid points of the mesh, we introduce the following notations:

$$\begin{cases} \phi_k(x_i, t^n) = \phi_{k,i}^n & k \in \{1, 2\} \\ \lambda_{k,i} = \lambda_k(x_i), & k \in \{1, 2\} \\ c_i = c(x_i) \end{cases}$$

4.1 First study case: without the source terms

System (1) is expressed in discrete form as:

$$\begin{cases} \frac{\phi_{1,i}^{n+1} - \phi_{1,i}^n}{\Delta t} = \lambda_{1,i} \frac{\phi_{1,i+1}^n - \phi_{1,i}^n}{\Delta x} + c_i \lambda_{2,i} \frac{\phi_{2,i+1}^n - \phi_{2,i}^n}{\Delta x} \\ \frac{\phi_{2,i}^{n+1} - \phi_{2,i}^n}{\Delta t} = \lambda_{2,i} \frac{\phi_{2,i+1}^n - \phi_{2,i}^n}{\Delta x} \end{cases}$$
(19)

Setting:

$$\gamma_{1,i} = \frac{\lambda_{1,i}\Delta t}{\Delta x}, \quad \gamma_{2,i} = \frac{c_i\lambda_{2,i}\Delta t}{\Delta x}$$
 we get the numerical scheme :

$$\phi_{1,i}^{n+1} = (1 - \gamma_{1,i})\phi_{1,i}^{n} + \gamma_{1,i}\phi_{1,i+1}^{n} - \gamma_{2,i}\phi_{2,i}^{n} + \gamma_{2,i}\phi_{2,i+1}^{n}$$
 (20)

$$\phi_{2,i}^{n+1} = (1 - \gamma_{2,i})\phi_{2,i}^n + \gamma_{2,i}\phi_{2,i+1}^n$$
(21)

Lemma 1. The numerical scheme (17)-(18) is stable 1 under the following Courant-Friedrichs-Lewy (CFL) condition:

$$\Delta t \le \min(\frac{\Delta x}{\overline{\lambda}_1}, \frac{\Delta x}{\overline{\lambda}_2})$$
 (22)

Let us now consider system (1) with:

$$\lambda_1(x) = \begin{cases} 10, & x < \frac{1}{2} \\ -4(x - \frac{1}{2})^2 + 10 & \frac{1}{2} \le x \le 1 \end{cases}$$

$$\lambda_2(x) = \begin{cases} 10, & x < \frac{1}{2} \\ 4(x - \frac{1}{2})^2 + 10 & \frac{1}{2} \le x \le 1 \end{cases}$$

$$c(x) = x + 4, D = \begin{bmatrix} \frac{1}{2} & 1 \\ 0 & \frac{1}{2} \end{bmatrix}, \phi_1^0(x) = 0, \phi_2^0(x) = \frac{x^2}{2}(1 - \frac{x}{3}) - \frac{2}{3}.$$

In this example, $\lambda_1(x) = \lambda_2(x)$ for $x \in [0, \frac{1}{2}]$, which makes the system weakly hyperbolic.

Fig.1 gives the time-space evolution of the two state variables ϕ_1 and ϕ_2 . The time evolution of $\frac{\|\phi\|_X^2}{\|\phi^0\|_X^2}$ is given in Fig.2.




Fig. 1. State ϕ_1 over (x,t) plane, (final time T=2s)




Fig. 2. Time evolution of $\frac{\|\phi\|_X^2}{\|\phi^0\|_X^2}$ in logarithmic scale

Both states are stabilized to zero as time grows up, the simulations are carried out using the numerical scheme (17)-(18) for 500 grid points in space, with CFL=0.9.

Here, regarding Theorem 1, the assumption

$$\max(D_{11}^2,D_{22}^2) = \frac{1}{4} < 1 - \frac{\overline{\lambda_2'}}{\overline{\lambda_2}} = \frac{3}{5}$$

is satisfied. Thus, the numerical result corroborates the theoretical one. Theoretically, we expect a decay rate given

¹ The method must be stable in some appropriate sense, meaning that the small errors made in each time step do not grow too fast in later time steps

by $\delta_{th} = \min\{\bar{\nu}\overline{\lambda_1}, \bar{\nu}\overline{\lambda_2}, \frac{\bar{\nu}-\nu}{1+\nu}\overline{\lambda_2}\} = \frac{7}{2}$ whereas, numerically, we found $\delta_{num} = 14.71 > \delta_{th}$. The difference is due to the conservatism introduced by the proposed Lyapunov analysis.

4.2 Second study case: with the source term

The numerical scheme when adding the source term is written as:

$$\phi_{1,i}^{n+1} = (1 - \gamma_{1,i})\phi_{1,i}^{n} + \gamma_{1,i}\phi_{1,i+1}^{n} - \gamma_{2,i}\phi_{2,i}^{n} + \gamma_{2,i}\phi_{2,i+1}^{n}$$

$$+ \Delta t(\lambda_{1,i}B_{11,i}\phi_{1,i}^{n} + \lambda_{1,i}B_{12,i}\phi_{2,i}^{n})$$
(20)

$$\phi_{2,i}^{n+1} = (1 - \gamma_{2,i})\phi_{2,i}^n + \gamma_{2,i}\phi_{2,i+1}^n + \Delta t\lambda_{2,i}B_{22,i}\phi_{2,i}^n \quad (21)$$

Let us now consider system (1) with λ_1 , λ_2 , c, D and initial conditions that are similar to first example but with

a source term $B = \begin{bmatrix} \frac{x}{6} & c(x) \\ 0 & \frac{x}{6} \end{bmatrix}$




Fig. 3. State ϕ_1 over (x,t) plane, (final time T=2s)




Fig. 4. Time evolution of $\frac{\|\phi\|_X^2}{\|\phi^0\|_X^2}$ in logarithmic scale

In this situation both states are also stabilized to zero as time grows up. The simulations are carried out using the numerical scheme (20)-(21) for 500 grid points in space, with CFL= 0.9.

Here, regarding Theorem 2, the assumption:

$$\max(D_{11}^2,D_{22}^2) = \frac{1}{4} < 1 - \max\left\{2\overline{B_{11}}, \frac{\overline{\lambda_2'}}{\underline{\lambda_2}} + 2\overline{B_{22}}\right\} = \frac{4}{15} \text{ is satisfied. As stated by Theorem 2, exponential stability is}$$

guaranteed with a decay rate at least equal to $\delta_{th} = 0.16$. Hopefully, the numerical result leads to a decay rate of

$$\delta_{num} = 12.89 > \delta_{th}$$

which is better than expected. This confirms the encouraging approach currently proposed by our Lyapunov functionals.

Remark 6. Several other tests have been carried out, particularly in the case where matrices D and B have a non-null under diagonal element (which we denote respectively D_{21}, B_{21} , for such situations system (1) is always unstable. We conjecture that closing the loop has a destabilizing effect.

5. CONCLUSIONS

To study the stability of weakly hyperbolic systems, where the principal part is non-uniform and non-diagonalizable everywhere, we return to the non-trivial study of triangular structures. Based on a Lyapunov analysis in the $L^2 \times H^1$ norm, two sufficient conditions for exponential stability emerge: the velocity and source terms have to be small in front of the edge back-reaction. Our refined analysis also allows us to specify upper bounds for decay rate and overshoot values, as illustrated in numerical simulations.

Upcoming works will be dedicated to a non-diagonal Lyapunov functional (full matrix P) to reduce the conservatism and tackle the case of systems where D_{21} and B_{21} are non null (full matrices B, D). Applications to some real physical systems will also be considered in the future.

REFERENCES

Alabau-Boussouira, F. (2002). Indirect boundary stabilization of weakly coupled hyperbolic systems. *SIAM Journal on Control and Optimization*, 41(2), 511–541.

Bastin, G. and Coron, J.M. (2016). Stability and boundary stabilization of 1-d hyperbolic systems, volume 88. Springer.

Bresch-Pietri, D. and Krstic, M. (2014). Adaptive output feedback for oil drilling stick-slip instability modeled by wave pde with anti-damped dynamic boundary. In 2014 American Control Conference, 386–391. IEEE.

Bribiesca-Argomedo, F. and Krstic, M. (2015). Backstepping-forwarding control and observation for hyperbolic pdes with fredholm integrals. *IEEE Transactions on Automatic Control*, 60(8), 2145–2160.

Coron, J.M., Vazquez, R., Krstic, M., and Bastin, G. (2013). Local exponential h^2 stabilization of a 2 × 2 quasilinear hyperbolic system using backstepping. SIAM Journal on Control and Optimization, 51(3), 2005–2035.

Diagne, A., Bastin, G., and Coron, J.M. (2012). Lyapunov exponential stability of 1-d linear hyperbolic systems of balance laws. *Automatica*, 48(1), 109–114.

Garetto, C., Jäh, C., and Ruzhansky, M. (2018). Hyperbolic systems with non-diagonalisable principal part and variable multiplicities, i: well-posedness. *Mathematische Annalen*, 372(3-4), 1597–1629.

Kharitonov, V. (2012). Time-delay systems: Lyapunov functionals and matrices. Springer Science & Business Media

- Krstic, M. (2009). Delay compensation for nonlinear, adaptive, and PDE systems. Springer.
- Lamare, P.O., Girard, A., and Prieur, C. (2016). An optimisation approach for stability analysis and controller synthesis of linear hyperbolic systems. *ESAIM: Control, Optimisation and Calculus of Variations*, 22(4), 1236–1263.
- LeVeque, R.J. (2002). Finite Volume Methods for Hyperbolic Problems. Cambridge Texts in Applied Mathematics. Cambridge University Press.
- Métivier, G. and Zumbrun, K. (2005). Hyperbolic boundary value problems for symmetric systems with variable multiplicities. *Journal of Differential Equations*, 211(1), 61–134.
- Prieur, C. and Mazenc, F. (2012). Iss-lyapunov functions for time-varying hyperbolic systems of balance laws. *Mathematics of Control, Signals, and Systems*, 24(1-2), 111–134.
- Valentin, C., Lagoutière, F., Choubert, J.M., Couenne, F., and Jallut, C. (2023). Knowledge-based model and simulations to support decision making in wastewater treatment processes. In A.C. Kokossis, M.C. Georgiadis, and E. Pistikopoulos (eds.), 33rd European Symposium on Computer Aided Process Engineering, volume 52 of Computer Aided Chemical Engineering, 703–708. Elsevier.